

CHANDELIER FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1, Thread the Nipple-1 to the Cross Bar, and tighten with the Washer and the Hex Nut.
- 2, Attach the Cross Bar to the Outlet Box by using 2 pcs Mounting Screws upwards.
- 3, Insert one end of the ARM to the Housing then attach the other end of Arm to the Center Tube, and then secure with the Ball Nuts. Thread the Center Tube to the Nipple-2.
- 4, Put the CAP onto the Nipple then screw by the Loop.
- 4, Choose a certain length of the Chain you need, and run the Fixture Wire and the Ground Wire through the chain links. Spread one end link of chain to clamp securely to the Loop.
- 5, Thread the Fixture Wire and Ground Wire through the Top nut, Collar Loop, Canopy, Nipple-1 and Cross Bar in order. Secure the Collar Loop to the Nipple-1 and then clamp the other end of the chain link to the Collar Loop.

Make wire connections:

- Smooth wire (w/markings) from the light to black wire from power source.
- Ribbed wire (w/o markings) from the light to white wire from power source
- Attach the ground wire to the cross bar with a green ground screw. Carefully tuck wire back into the outlet box.

- 6, Attach the Canopy to the Cross Bar by inserting the Collar Loop, and then tighten with the Top Nut.
 - 7, Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).
 - 8, Thread the Nipple-3 to the Hex Nut-1, then secure them with Hex Nut-2. Attach the Cover-1, Cover-2, Metal Ball in order and secure with the Finial.
- Turn on the power at fuse or circuit box.

