




Push Drain with Overflow Installation Instructions




NOTICE

Failure to follow all directions may cause leaks
which may result in water damage

www.kingstonbrass.com

TOLL-FREE CUSTOMER SERVICE: 1-877-2-KBRASS
TECHNICAL SUPPORT E-mail: service@kingstonbrass.com
12775 Reservoir Street, Chino, CA 91710

Tools Required




Basin Wrench




Adjustable Wrench



Teflon Tape



Silicone Sealant



Screwdriver

Installation Steps:

1. Remove the lock nut (6), washer (5) and rubber gasket (4) from the drain body (2).
Push rubber gasket (3) upwardly against the underside of flange of drain body (2).
2. Insert the drain assembly (1)/(2)/(3)/(7) downwardly through the drain opening on the bottom of sink. So the tailpiece (7) and the outer threads of drain body (2) can go all the way through the drain opening and expose beneath the sink.
3. Adjust rubber gasket (3) to fit in the drain opening snugly. Make sure the taper-surface side of the rubber gasket (3) is downward.
4. Install rubber gasket (4), washer (5) and lock nut (6) upwardly onto the drain body (2) from the end of tailpiece(7). Make sure the taper-surface side of the rubber gasket (4) is upward.
5. Slowly tighten up the lock nut (6) with a wrench until the rubber gasket (4) can completely and tightly seal the drain opening beneath the sink.
6. Turn the tailpiece (7) by hand to remove it from drain body (2).
Apply Teflon tape on the threads of tailpiece (7). Then re-connect it tightly with drain body (2).
7. Push the stopper (1) to the closed position of the drain body (2), then turn on the faucet to fully fill the sink with water. Examine and ensure that no water is leaking from the tailpiece (7).
8. Push the stopper (1) to the open position to drain water, examine to make sure no water leakage around the rubber gasket (4) or connection with tailpiece (7).
If leakage found, adjust the rubber gasket (4) and re-tighten up the lock nut (6) until no more leakage.

