## ADJUSTABLE STEEL GANTRY CRANE - KNOCKDOWN - AHSN-6-15-10 APPROX WEIGHT: 931.45 lbs. \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON - 179 3/4" -10 1/8" 131 11/16" 121" MAX 79" MIN 3D VIEW FOR REFERENCE ONLY **◄**── 64 5/16" **──►** DIMENSION TOLERANCE ± 1/4" STANDARD FFATURES I. THE UNDERSIGNED. AGREE THAT THE PRODUCT AS SPECIAL FEATURES REPRESENTED SATISFIES DESIGN AND DIMENSION MODEL NUMBER IS AHSN-6-15-10 **NONE** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α CONFIRM PRODUCT AND INSTALLATION CAPACITY IS 6,000 LBS. P COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE BASE WIDTH IS 64 5/16" P AND LOCAL REGULATIONS AND STANDARDS. R MAX OVERALL HEIGHT IS 131 11/16" ANY MODIFIED UNITS ARE NON-RETURNABLE 0 I-BEAM HEIGHT IS 10 1/8" [ ] As drawn [ ] As marked I-BEAM FLANGE WIDTH IS 4" Signed: Date: OVERALL I-BEAM LENGTH IS 179 3/4" Printed Name: USABLE I-BEAM LENGTH IS 149 3/4" LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING ADJUSTABLE UNDER I-BEAM HEIGHT DISTRIBUTOR'S NAME: 121" MAX FOR INTERNAL USE ONLY W.O.# X PROJECT SIGN OFF VESTIL MANUFACTURING 79" MIN **SALES** HEIGHT IS ADJUSTABLE IN 6" INCREMENTS DATE: 07/22/2014 SALES: X CASTERS: (4) Ø8" X 3" WIDE PHENOLIC ENG. reference: X SWIVEL CASTERS WITH FOUR SCALE: 1:40 FILE NAME: FAB. LOCKING POSITIONS QUOTED LEAD TIME: $_{ m Y}$ QUOTE # 28-007-327

POWER

Χ