

ASSEMBLY INSTRUCTIONS

Pendant lamp - Model 61140-11



Parts:

A: Nipple	E: Metal Loop	I: Mounting Screw
B: Tube	F: Round Nut	J: Tube
C: Flat Washer	G: Fixture Canopy	
D: Shade	H: Universal Crossbar	

INSTALLATION

1. Carefully unpack and identify all parts.
2. Install the wire from nipple go through Stem(B), Flat Washer (C), Shade (D), then secure with Metal loop(E)
3. Screw the Adjustable Stem (B) onto the Nipple (A). The height of Tube (B) can be adjusted by adding tubes (J1, J2, J3, J4).
4. Attach the Universal Crossbar (H) to the outlet box using the two Mounting Screws (I). The side of the Mounting Plate marked "GND" must face out.
5. Using the wire nuts provided, connect the white wire from the fixture to the white wire of the outlet box, connect the black wire from the fixture to the black wire of the outlet box, and then connect the ground wire from the fixture to the ground wire of the outlet box.
6. Place the Fixture Canopy (G) over the Universal Crossbar (H), and allow the Mounting Screw (I) to go through the Fixture Canopy (G), then secure the Fixture Canopy using the Round Nuts (F).
7. If adding a Shade (D) slide spht washer onto Nipple(A) and tighten (Flat washers to hold tightly)

