

PERFORMANCE DATA SHEET

SPECIFICATIONS AND OPERATIONAL LIMITS

Rated service flow	2.0 gpm / 7.6 lpm
Capacity	10,000 gallons / 38,000 liters
Operating pressure range	40–100 psi / 280–690 kPa
Operating temperature range	40°–120° F / 4°–49° C

This system has been tested according to NSF/ANSI 177 for the reduction of free available chlorine. The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 177. The system has not been evaluated for free available chlorine reduction performance in the presence of chloramines. Free available chlorine reduction performance may be impacted by the presence of chloramines in the water supply. Please contact your local water utility to determine if chloramines are used in treating your water.

Testing was performed under standard laboratory conditions. Actual performance may vary.

PARAMETER	INFLUENT CHALLENGE	MINIMUM CHLORINE REDUCTION
Free Available Chlorine (FAC)	2mg/L FAC	≥ 50% FAC

GENERAL INSTALLATION/OPERATION/MAINTENANCE REQUIREMENTS

- Install in compliance with state and local laws and regulations.
- Filter Cartridge should be replaced when rated capacity is reached, or when there is a reduction of flow.
- The system is not to be used for drinking water purposes.

Brondell VivaSpring Filtered Shower Head Model #FSH25
Replacement Filter Cartridge Model #FF-15



System Tested and Certified by IAPMO against NSF/ANSI Standard 177 for the reduction of free available Chlorine (FAC).
Also tested to ASME A112.18.1-2012/ CSA B125.1-12.



System tested and certified to meet or exceed EPA Watersense guidelines for water efficiency.