

Project:

# Spec Sheet

Description: Surface-mounted lights are neatly compact and solidly built. They offer a range of lens variations within the tightly defined geometry of their die-cast rings. Also available as a [Downlight Sconce](#), [Up/Down Sconce](#), [Bollard](#), and [Double Bollard](#).



Type #:

## Dimensions

Height: 2.5"  
Diameter: 5"  
Canopy/Backplate/Base: 5"

## Electrical Specs

Bulb(s) Included?: Yes  
Bulb 1 Type: Integral LED  
Bulb Quantity: 1  
Input Voltage: 120VAC  
Wattage: 10  
Initial Lumens: 1040  
Color Temperature: 3000K  
CRI: 90  
Power Supply Type: Driver  
Power Supply Quantity: 1  
Power Supply Location: Outlet Box  
Dimming Type: TRIAC/ELV  
Bulb Max Wattage: 10

## Installation

Installation: Licensed electrician required

## Shipping

Carton 1 L x W x H: 9" X 9" X 6"  
Carton 1 Gross Weight: 3 LBS  
Fixture Weight: 2

## Shade

Lens Type: Clear Cylinder Lens  
Shade 1 Material: Clear Polycarbonate

## Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

## General Listings

Features: Wet Rated  
Certification: C-ETL-US  
Color/Finish: Textured Bronze (.72)  
Dark Sky Friendly: N