



Installation Steps:

Thank you for using our products. Please read the operating instructions before installation. Keep these instructions for reference. Disconnect the power supply before installing this product. Installation by a professional electrician is recommended.

1. Fix the mounting bracket in the reserved mounting box.
2. Connect the black wire to the fire wire with a wire cap and the white wire to the zero wire with a wire cap and wrap tightly with insulating tape. Connect the fixture ground wire to the junction box ground wire. If the house does not have a ground wire, connect it to the green screw on the siding. (Screw labeled GND).
3. Secure the bulb to the suspension plate with the round head nut.
4. Attach the bulb to the light head, making sure to make good contact.
5. Install the glass lampshade in the lamp head position.

Attention:

1. The input power of the lamp is AC 120V 50Hz.
2. Any behavior that violates residential fire protection regulations is prohibited.
3. Under no circumstances should the lamps be covered with heat insulation pads or wooden materials.
4. Before maintenance, make sure that the power supply of the lamp has been cut off and the light source has cooled down. Before powering on, make sure that the light source and the lamp holder are connected correctly.
5. Please wipe with a towel or flannel, and clean the lamp body with a non-corrosive detergent. Do not scrub directly, wipe with water or a damp cloth.
6. If you have any questions about this manual, please consult a qualified lighting installation engineer.