

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact: \_\_\_\_\_

LED Ceiling/Wall • Wet location listed



## Specifications:

### Description:

This collection features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

### Construction:

White (-30) (powdercoat)  
Aluminum construction  
LED Module is replaceable  
Flicker-free dimming to 10% brightness with most ELV type dimmers  
(See Dimming Notes)  
Title 24 compliant  
Unit covers a standard 4" hexagonal recessed outlet box  
Mounting strap for outlet box included

### Performance:


Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Labels	cCSAus Wet location listed ENERGY STAR® qualified

### Images:



### Dimensions:

Width: 6-1/4"  
Height: 10-5/8"  
Depth: 4-3/8"  
H/CTR: 5-1/4"



### Catalog number:

Base	Finish	Color Temp	CRI
	30 - White	- 3000K	- 90 CRI



## Dimming Notes:

---

This collection is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

### Electronic Low Voltage ELV Reverse Phase Controls

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

---