

Features

- ExoCrylic™
- Oval shape
- Drop-in installation
- Six individually adjustable ProFlex® hydro-massage jets
- Pump with air switch and grounding-type plug-in cord
- Molded lumbar support and armrests for comfort
- Optional K-9696 whirlpool trim kit in additional finishes



Codes/Standards

ASME A112.19.7/CSA B45.10
CSA B45.5/IAPMO Z124
UL 1795
CSA 22.2 No. 218.2

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond



Technical drawings of the 60-inch oval whirlpool bathtub, including dimensions in inches and millimeters:

- Top View:**
 - Overall Length: 60" (1524 mm)
 - Overall Width: 20" (508 mm)
 - Front Panel Width: 3-1/8" (79 mm)
 - Front Panel Depth: 8" (203 mm)
 - Side Panel Depth: 1" (25 mm)
 - Lumbar Angle: 21°
- Side View:**
 - Front Panel Height: 2-1/2" (64 mm)
 - Front Panel Thickness: 3" (76 mm)
 - Front Panel Depth: 2-7/8" (73 mm)
 - Side Panel Height: 3/8" (10 mm)
- End View:**
 - Overall Width: 40" (1016 mm)
 - Front Panel Height: 17-5/8" (448 mm)
 - Side Panel Height: 16-1/8" (410 mm)
 - Front Panel Thickness: 1-1/2" Bath Drain
- Required Pump/Control Access:** 20" (508 mm) W x 15" (381 mm) H
- Drop-In Rim Detail:** 1-1/2" (38 mm)

Installation:	Drop-in
Drain location:	Reversible
Basin area, bottom:	46" x 19" (1168 mm x 483 mm)
Basin area, top:	55" x 29" (1397 mm x 737 mm)
Weight:	56 lbs (25.4 kg)
Minimum floor load:	30 lbs/ft ² (146.5 kg/m ²)
Water depth:	14" (356 mm)
Water capacity:	54 gal (204.4 L)
Template:	Drop-in, 114859-7, required, not included
Electrical rating:	Pump: 120 V, 7.5 A, 60 Hz

The suction line extends 1" (25 mm) beyond the edge of the rim. The pump base extends 1-1/8" (29 mm) beyond the edge of the rim. Modify the framing as needed.