








Wire-Adjustable Lamp


Instructions

NOTE :

1. Please Check whether the accessories are missing in time after unpacking. (Bulbs not included)
2. We offer 12 months guarantee. If you find any damaged or missing parts in transit, please feel free to contact us by email , we will solve it ASAP!




01




02

Screw the Mounting Bracket to the ceiling or junction box . (There are many gaps, you can screw it to the wall.)




* ceiling fixing screws






03

Screw the ceiling plate to the ceiling, Fixture wires should be connected to ceiling wires by color, black wire to be attached to the black wire, white to white and ground wire to ground wire.



For your safety, you should use wire connector T1 or T2 as you like, if you choose connector T1, you need to use electric tape for it.



04

Fix the light to the ceiling



Poles-Adjustable Lamp

INSTRUCTIONS

(* Please turn off the breaker before starting the installation.)

NOTE :1. Please Check whether the accessories are missing in time after unpacking. (Bulbs not included)

2. We offer 12 months guarantee. If you find any damaged or missing parts in transit, please feel free to contact us by email , we will solve it ASAP!




01




02

Screw the Mounting Bracket to the ceiling or ceiling box. (There are many gaps, you can screw it to the ceiling)




If you install the Mounting Bracket into the electrical box, please use T6 to fix it instead of T5




03

Fixture wires should be connected to ceiling wires by color, black wire to be attached to the black wire, white to white and ground wire to ground wire.




04

Fix the light to the ceiling




Wiring Instruction

T1



Wire nuts



Crimp terminal

T2




T3



T1

Wire nuts




Tips:

Screw the twisted electric wire completely into the terminal until it does not loosen.

T1

Crimp terminal




*** Pliers not included.***

Tips:

Use crimping pliers to ensure the wire are fastened to the terminal.

T2




*** Screwdriver not included.***

Tips:

Loosen the small screw, insert the wire, and tighten the screw.

T3



*** Heat gun NOT included.***

Tips:

1. Hold the heat gun about 3~6 inches away from the tubing, and keep it moving back and forth.
2. Continue heating the tubing until it is tightly secured to the wire.