

TRIMMED HOUSING

4.5" Volta

WAC LIGHTING

Responsible Lighting®

SPECIFICATIONS

- Input:** Universal 120 - 277V AC 50/60 Hz
- Standards:** ETL & cETL, Chicago Plenum, IC-rated, Airtight (see below for list)
- Dimming:** Electronic Low Voltage (ELV): 100%-5% (120V only)
0-10V: 100%-0% (120 - 277V)
- Emergency:** EM fixtures provided with integral Emergency battery back up with 24" lead wire remote test switch. Provides at least 90 minutes of 5W illumination during emergency operation.
- Mounting:** New construction housings included with universal mounting brackets and hanger bars
Ceiling cut out (Round): Ø 5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
See next page for ceiling thickness information

Fixture Type:

Catalog Number:


Project: _____

Location: _____


Construction: 20 Gauge cold rolled steel

Warranty: 5 year WAC Lighting product warranty


Round New Construction



Square New Construction



Remodel



HOUSINGS

	Model	Power*	S	N, F, W, A	Rating	Emergency Backup	Compatible Trims
Round New Construction	R4RNT Airtight	15	10W	15W	IC rated	EM Emergency backup battery (OPTIONAL)	R4RD2T
	R4RCT Airtight, Chicago Plenum	25	15W	25W	IC rated		R4RD1T
		36	23W	36W	Non-IC		R4RAT R4RWT
Square New Construction	R4SNT Airtight	15	10W	15W	IC rated	EM Emergency backup battery (OPTIONAL)	R4SD2T
	R4SCT Airtight, Chicago Plenum	25	15W	25W	IC rated		R4SD1T
		36	23W	36W	Non-IC		R4SAT R4SWT
Remodel	R4BRT Round or Square	15	10W	15W	Non-IC	N/A	R4RD2T, R4SD2T
		25	15W	25W	Non-IC		R4RD1T, R4SD1T
		36	23W	36W	Non-IC		R4RAT, R4SAT R4RWT, R4SWT

*Power consumption depends on beam angle of the trim.

R4 _____
Example: **R4RNT-15** or **R4RNT-15EM** (with Emergency backup battery)

Field Replaceable Driver

- D-R4N-15** Driver for 15W New Construction Hsg
- D-R4N-25** Driver for 25W New Construction Hsg
- D-R4N-36** Driver for 36W New Construction Hsg

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TRIMMED HOUSING

4.5" Volta

WAC LIGHTING

Responsible Lighting®

CEILING THICKNESS BY TRIM

Trim Model	Trim Description	Ceiling Thickness		
		1/2"	1"	1 1/2"
R4RD2T R4SD2T	<i>Downlight</i>	Yes	Yes	Yes
R4RD1T R4SD1T	<i>Shallow Regressed Downlight</i>	Yes	Yes	Yes
R4RAT R4SAT	<i>Adjustable</i>	Yes, to 45°	Yes, to 45°	Yes, to 35°
R4RWT R4SWT	<i>Wall Wash</i>	Yes	Yes	No

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760