



## PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

## IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

## INSTALLATION STEPS:

1. Thread the rod through the wire, twist them tightly and then lock them with the lamp supporting.
2. Lock the four elbow bend pipes in the side hole of the lamp supporting.
3. Cover the lid of the lamp supporting and lock the round ring.
4. Place the four bend iron sheets on the rubber sheet, then lock the screws.
5. Thread the cable and the ground wire into the chain and the ceiling plate, then fasten the button.
6. Twist the ceiling plate into the junction box, then connect the ground wire.
7. Connect the black wire of the light to the live wire, and the white wire to the neutral wire, tighten them with the lid. Pay attention that don't expose the wire. Wrap the insulation tape, and carefully plug the wires into the junction box.
8. Install the ceiling plate, tighten the screws.
9. Install the E26 bulb. (not included)