



## General Information

Type	surface-mounted light
Product segment	Indoor
Theme	EGLO connect.z
FSC®	FSC® Mix70% Hevea br FSC® C152762

## Dimensions

Article Height (in mm)	28
Article Length (in mm)	225
Net Weight (in kg)	0.78 Kilogram
Article Overhang (in mm)	85
Article Width (in mm)	135
Article Diameter (in mm)	285
Canopyens længde (i mm)	400
Canopyens bredde (i mm)	45
Canopyens højde (i mm)	45
Base Diameter (in mm)	160
Base Length (in mm)	240
Base Width (in mm)	160
Installation Depth (in mm)	26
Cutout (in mm)	205

## Material & Colour

Enclosure Material	aluminium
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	textil-cable black

## Functionality

Switch Type	without switch
Battery	No
Function	control via APP + remote control CCT
Battery Type	Li-ion; 1200mAh
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

## Technical Information

Protection Degree	IP44
Protection Class	2
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	19,5W
Dimmable	Yes
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz

## Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

## Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	2700-6500K
Light colour Complete	TUNEABLE WHITE
Nominal Lifetime (in h)	5000
Tænd-/slukcyklusser	15000
Energy efficiency class (EEI)	E
Dimmable	Yes
Info changeability□light source/driver	LED + driver cannot be exchanged
Lyskildens faktiske effekt (0,1 W præcision)	18
Farvetolerance (LED, SDCM)	<6
Lumen Complete	2500

## Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

