


| Toilet wall-mounted | Dimension | Weight | Order number |
|--|------------------------|---------|--------------|
| washdown model, suitable for SensoWash Starck, Durafix included, cUPC® listed*, WaterSense® listed | | | |
| Colors | | | |
| 00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness) | | | |
| Variant | | | |
| ♣ 1.6/0.8 gpf | 14 1/8" x 24 3/8" Inch | 64 lb | 222609..92 |
| ♣ 1.6/0.8 gpf | 14 1/8" x 24 3/8" Inch | 64 lb | 222609..92 |
| Infobox | | | |
| Durafix for concealed installation is included, * Complies with following standards: ASME A112.19.2/CSA B45.1 and ASME A112.19.14, For suitable SensoWash® shower-toilet seats, please see matrix on page xxx, Wall-mounted toilet is ADA compliant, when installed with a seat height of 17" - 19" from the finished floor, Not available with WonderGliss, In-wall tank & carrier and actuator plate required for installation | | | |
| Noise reduction gasket for wall-mounted toilet | | 0.7 lb | 005020 |
| Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, dual flush, mounting frame, mounting hardware included, push rods, front plate plastic | 8 1/2" x 5 3/4" Inch | 0.7 lb | WD5008 |
| Toilet in-wall tank & carrier, Standard WaterSense® listed, For 2"x4" and 2"x6" wall installation, for toilets with a projection of <= 24 5/8", adjustable feet 0" - 9 1/2", SensoWash ready, mechanical front flush actuation, includes in-wall tank, marking of filling height, dual flush, insulated against condensation, Scope of delivery, HDPE wall-mounted toilet connection bend DN 90/90, PE wall-mounted toilet connection set DN 90, wall-mounted mounting rods M12, mounting hardware included, 2 bolt caps, cUPC® listed*, Load capacity = 880 lbs | 23 1/4" x 45 1/4" Inch | 35.3 lb | WD1022 |

Starck 3 Toilet wall-mounted  # 222609..92 / 222609..92

|< 14 1/8" Inch >|

| Suitable products | |
|--|--------|
| Toilet seat and cover elongated, hinges stainless steel, removable, with slow close, | 006339 |
| SensoWash® Starck shower-toilet seat for Starck 2, Starck 3 and Darling New* Rear-, Lady- and Comfortwash, individual adjustment of water-, air- and seat surface temperature as well as nozzle position and jet strength, power actuated lid and seat, night light, 2 individually programmable user profiles, remote control included, self-cleaning wand, on / off-button, Quick release: easy seat unit removal and attachment, 14 5/8" x 20 1/4" Inch | 610000 |
| Toilet seat ring elongated, open front, hinges plastic, without slow close, | 006431 |
| Toilet seat ring elongated, open front, hinges plastic, with slow close, | 006439 |
| Toilet seat and cover elongated, hinges stainless steel, without slow close, | 006332 |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.