



## 60W Low Bay LED Retrofit Lamp-5000K

**Item # 667**

**L60T170 5000K**

### 1 LAMP SPECIFICATION

1-1	Lamp Type	Low Bay LED Retrofit Lamp
1-2	Dimmable (Y/N)	No
1-3	Base	E39
1-4	Lamp Finish/Type	Long Neck T170
1-5	Lamp Wattage	60W
1-6	Wattage Comparison (FC on Floor)	upto 175W MH
1-7	Rated Average Life (hours) L70	50,000
1-9	Reliable Operating Temperature	-4°F to 113°F



### 2 Photometric Characteristics

2-1	Initial Lumens	6000
2-2	Centre Beam Candle Power (Cd)	1500
2-3	Beam Angle (50% I Max) in Degree	125
2-4	Beam Angle (10% I Max) in Degree	155
2-5	Initial Lumens per Watt	100
2-6	Color Temperature	5000K
2-7	Color Rendering Index (CRI)	80



### 3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V/277V- 50/60Hz	3-2	Power Factor	>0.9
3-3	Lamp rated Wattage	60W	3-4	Input Line Current	520mA@120V 240mA@277V
3-5	Total Harmonic Distortion	≤20%	3-6	Dimming Range in %	Non Dimmable

### 4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	9.055 / 230	4-2	Diameter (Inches/mm)	6.693 / 170
-----	----------------------------	-------------	-----	----------------------	-------------

### 5 Product Information

5-1	Description	60W Low Bay LED Retrofit Lamp-5000K			
5-2	Primary Application	Commercial and Industrial use			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	DLC/LM79	5-8	UL / FCC	YES

### 6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	7.1 X 7.1 X 9.8	6-2	Inner Carton Size (Inches)	N.A
6-3	Master Carton Size (Inches)	1x6	22.05 x 14.76 x 10.63	6-4	Gross Weight / Net Weight (lbs)	11.68 / 4.85

02/2018© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.