

A70G Table instructions on how to build rectangular stainless steel table with marble top

1. The gold stainless steel table base can work with either side being the top.
2. The black rubber stoppers with silver screws on them are for the bottom of the table whichever side you choose to be the bottom is fine and it is best to install these first before flipping over to the other side to install the table top (the gold rectangular ring without the marble top).
3. The gold metal rectangular table ring needs to have the long gold bar in the middle that runs across the 72" length of the table to be facing up. Please see photos to aid in this understanding so you can see which side is up.
4. The screws provided need to be lined up with all the holes and need to be screws down simultaneously. (Meaning 4 people line them up together and screw them down together at the same time). If only one, two or 3 people are available to do the assembly job instead of 4, then that person should not screw down each screw tightly one at a time. This will cause the other holes to run out of alignment. You screw in only one thread at a time. Some screws may be a bit sideways in the beginning but stainless steel is a bending and slightly forgiving and bendable (moving) metal. If you force down screws one at a time all the way, it will never work. You have to go around screwing them down a little at a time which can take longer than usual if only one person is available to screw it down. After first screw and second screw is slightly inserted (only one or two threads just enough for them to hold them position, not tightened down yet, you may need to gently force the third and fourth screws into alignment and into position and even though slightly sideways, they should be able to catch some threading. You can then tighten them a little more than the original two screws to bring them straight and into better position. Once all 4 screws are worked in about halfway, it should be o.k. to screw them down one at a time if you are alone doing this job.
5. Once all the screws are in and the table top ring is properly secured, it is time to measure all 4 corners of the table from the floor. If one side is higher than the other, you can easily adjust the table to be straighter by loosening or tightening the black rubber stoppers at bottom. These rubber table feet are for adjusting the table to be perfectly level (or as level as you can get it) it doesn't need to be perfect (within a quarter inch or even half inch is fine). You can even adjust them without flipping the table with ring installed back down as long as someone is there to help lift up the table ever so slightly on the short (lower) side to allow one to slightly loosen the black knob (foot).
6. At last, you just lay the marble on top of the ring and push the edges into place as needed so the marble top is perfectly aligned with the ring. The marble is so heavy that it just stays in place and will never move out of position.