

ACT3061 - Single Lever

Product Finish: Matt Black

EAN13 barcode: 5060879992276



Product features:

- Metal construction throughout
- Single lever control for effortless single handed control
- Solid and functional European architect design styling
- Antisplash spout supplied as standard
- Supplied complete with flexible tail pipes for fast simple fitting


Additional information / Parts included:

1 x triangular stabilizer, 2.5mm Allen key, self adhesive sink seal (sco06030)

Primary WRAS fittings number (see www.wras.co.uk):

2010360

Product dimensions:




- Overall Height / projection: 317 mm
- Exit reach: 219 mm
- Exit height: 298 mm
- Centre distance(s): n/a
- Base diameter(s): 50 mm
- Recommended hole diameter: $\varnothing 35$ mm
- Max. surface depth: 70 mm
- Spout diameter: 30x10 mm
- Spout aerator size: M24

Packaged properties:

Box length: 435 mm
Box width: 340 mm
Tap only weight: 2.23 kg

Box depth: 70 mm
Units per outer: 5
Boxed weight: 2.84 kg

Product flow characteristics:



- Min / Max water pressure: 0.50 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 12.58

- Control valve type: 35mm \varnothing single lever ceramic cartridge
- Flow characteristics: Single flow
- Non return valve(s): Integral to Hot & Cold inlets

- Aerator type: Honeycomb aerator
- Spout connection method: Rear of body

- Tail pipe inlet / outlet size: M12 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 245 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year