



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11565** - 9 Watt; LED Direct Wire; Low Profile Regress Baffle Downlight; 4 Inch Square; Starfish IOT; Tunable White and RGB; 120 Volt; 90 CRI; White Finish

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



## ELECTRICAL

|                            |                                     |
|----------------------------|-------------------------------------|
| Technology:                | LED                                 |
| Watts:                     | 9W                                  |
| Volts:                     | 120V                                |
| Lumens:                    | 540L                                |
| CRI:                       | 90                                  |
| CCT (Kelvins):             | 2000K-5000K                         |
| Color Description:         | Warm to Cool White/Color Changeable |
| Beam Spread :              | 110                                 |
| Hours Rated:               | 50000                               |
| Dimmable:                  | Yes-Dimmable                        |
| Dimmable Down To %:        | 100 to 10 percent                   |
| DimmableText:              | Only with Starfish App              |
| Dimming Type :             | Smart-Starfish App only             |
| Incandescent Equivalent :  | 45W                                 |
| Operating Temperature :    | -20C (-4F) to +40C (+104F)          |
| Replaceable Light Source : | No                                  |
| Connection:                | Direct Wired                        |
| THD:                       | <30%                                |
| Power Factor :             | >0.9                                |
| Warranty:                  | 5 Year Limited - Fixtures           |

## PACKAGING

|                   |                       |
|-------------------|-----------------------|
| Each UPC:         | 045923115653          |
| Each Quantity:    | 1                     |
| Each Dimensions:  | 6.10 x 3.54 x 5.31    |
| Inner UPC:        | 20045923115657        |
| Inner Quantity:   | 0                     |
| Inner Dimensions: | 0.00 x 0.00 x 0.00    |
| Case UPC:         | 10045923115650        |
| Case Quantity:    | 20                    |
| Case Dimensions:  | 18.50 x 12.64 x 11.00 |

## INFO

|                    |   |
|--------------------|---|
| Installation Note: | Driver Dimensions: 3.46 Inches Long x 3.46 Inches Wide x 1.44 Inches High |
|--------------------|---|

## PHYSICAL

|                |                         |
|----------------|-------------------------|
| Finish:        | White                   |
| Lens Material: | Polycarbonate (PC)      |
| Finish Family: | White                   |
| Dimensions:    | L:5.00" W:5.00" H:1.25" |
| Weight (Lbs.): | 1.04                    |
| Material:      | Aluminum                |

## INSTALLATION

|                        |       |
|------------------------|-------|
| Max Drywall Thickness: | 1 in. |
|------------------------|-------|

## IOT

|                   |                                    |
|-------------------|------------------------------------|
| IOT Enabled:      | Yes                                |
| What's Supported: | Google Home;Alexa;Siri;SmartThings |

## COMPLIANCE

|                            |                                   |
|----------------------------|-----------------------------------|
| Safety Listing:            | cETLus                            |
| Location Rating:           | Wet                               |
| Indoor/Outdoor:            | Indoor                            |
| Energy Star Qualified:     | Yes                               |
| Energy Star Unique ID:     | ESID-2494954                      |
| Energy Star Lamp Category: | Downlight Recessed                |
| UL/ETL Standard:           | ANSI/UL 1598; CSA-C22.2 No. 250.0 |
| CA Prop 65:                | Lead                              |
| FCC Compliant:             | Yes                               |
| RoHS Compliant:            | Yes                               |
| SDS Class:                 | LED_Fixture                       |
| Restrictions:              | No Restrictions                   |

**ACCESSORIES**

---

**80-943**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter

---

**80-950**New Construction Mounting Plate for Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter

---

**80-986**6 Foot Remote Driver Extension Cable; 2-Pin; White Finish

---