



## ASSEMBLY INSTRUCTIONS Model 98-B5250 Pendant

**CAUTION:** A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT MUST INSTALL THIS FIXTURE IN ACCORDANCE WITH ALL APPLICABLE LOCAL CODES AND WITH FULL KNOWLEDGE OF THE HAZARDS INVOLVED.

**WARNING:** THE ELECTRICITY MUST BE DISCONNECTED AT THE MAIN FUSE BOX OR CIRCUIT BREAKER PANEL BEFORE INSTALLATION OF THIS PENDANT – TURNING THE POWER OFF USING THE LIGHT SWITCH IS NOT SUFFICIENT TO PREVENT ELECTRICAL SHOCK. THIS PENDANT IS NOT DESIGNED TO SUPPORT EXTERNAL WEIGHT OTHER THAN THE LAMP SHADE THAT IT IS PROVIDED WITH.

### Notes:

1. This pendant is constructed using 3-conductor electrical wire. The gold thread indicates the ground wire.

### Assembly Instructions

1. Select the required length shade mounting screws (A or B).
2. Insert each shade mounting screw through the corresponding hole in the shade and tighten securely to fixture collar.
3. Insert electrical wire and support cable thru canopy and bracket bar. Choose the desired drop length for the pendant and tighten support cable to bracket bar. Support cable carries the weight of the fixture. Make all electrical connections in accordance with all local electrical codes. Slide canopy up to ceiling and tighten setscrew to secure in place.

