Installation Instructions

TABLE LAMP

- 1. Put the **BOTTOM RING** on the table, then attach 3/4 while **LAMP SHADE CLOTH PLATE** around the **BOTTOM RING**.
- 2.Attach the TOP RING to the upper LAMP SHADE CLOTH PLATE and the rest 1/4 LAMP SHADE CLOTH PLATE to the BOTTOM RING. Then fix the place where the LAMP SHADE CLOTH PLATE is joined end to end
- Top ring Shade

 Top ring Shade

 Shade Bottom ring
- 3.Insert and thread the **TUBE** onto the **BASE** by turning clockwise until secure
- 4. Squeeze **HARP** together and insert into **SADDLE**.
- 5. Install Bulb (**NOT Included**) onto the **LAMPHOLDER** according to the wattage label.
- Place SHADE onto HARP and Tighten SHADE by FINIAL.

TIP: You can grasp the **FINIAL** and **FASTENER** together to adjust the **SHADE** to correct position if it is skew. **FASTENER** is slightly rotatable by external force.

CAUTION - Refer to the wattage caution label located on the **LAMPHOLDER** for recommended maximum wattage - **DO NOT** exceed recommended wattage. **WARNING** - Do not attempt to replace the bulb while the lamp is plugged into a wall receptacle.

IMPORTANT SAFETY INSTRUCTIONS

This portable lamp has a polarized plug (One blade is wider than the other) as a safety feature to reduce the risk of the electric shock. This plug will fit in a polarized outlet only one way. If the plug does not fit in the outlet, reverse the plug. If it still does not fit, consult a qualified electrician. Never use an extension cord unless the plug can be fully inserted. Do not alter the plug.



