

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

Bronze LED Outdoor Wall Cylinder

Wall mounted • Wet location listed



Description:

6" downlight wall cylinder. These series are ideal for a wide variety of interior and exterior applications including residential and commercial. The Cylinders feature a 120V alternating current source and eliminates the need for a traditional LED driver. This modular approach results in an encapsulated luminaire that unites performance, cost and safety benefits.

Specifications:

- Antique Bronze (Powder Coat Paint)
- Die cast and extruded aluminum Construction
- Interior finish matches exterior finish.
- 1,355 lumens 46 lumens/watt
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	30w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	909/30 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	Meets California Title 24 high efficacy requirements
	for outdoor use only

Images:



Dimensions:

Diameter: Width: 6"
Depth: 8-7/8"
Height: 12"
H/CTR: 4-1/2"

Bronze LED Outdoor Wall Cylinder


Wall mounted • Wet location listed



Photometrics:

Input Voltage	120 V
Input Frequency	60 Hz
Input Current	
Input Power	30
Power Factor	0.935
THD	<20%
FCC	FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

LED Light Engine: 3000 K 90 CRI CRI
System Wattage: 30
Fixture delivered lumens: 909
Fixture Efficacy: 30
Spacing Criteria: 1.1



CANDELA DISTRIBUTION

DEG	CANDELA	LUMENS
0	634	
5	632	60
15	605	170
25	528	240
35	346	217
45	187	145
55	71	64
65	9	11
75	1	2
85	0	0
90	0	

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	469	51.6
0-40	686	75.5
0-60	896	98.6
0-90	909	100.0
90-180	0	0.0
0-180	909	100.0



Dimming Notes:

This product is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P
Lutron Nova NTELV-300
Lutron Verti VTELV-600
Lutron MAELV-600
Lutron SPELV-600
Leviton AWRMG-EAW
Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.