

ACT2004 - Dual Handle Monobloc

Product Finish: Brushed Nickel

EAN13 barcode: 5060048383973



Product features:

- Metal construction throughout
- Quarter turn handle action for precise flow control
- Minimalist planate design form
- Antisplash spout supplied as standard
- Supplied with copper tail pipes for maximum stability and flow


Additional information / Parts included:

1 x metal horseshoe, 1 x rubber ring, 1 x fixing stud, 1 x fixing nut, 1 x rubber seal

Primary WRAS fittings number (see www.wras.co.uk):

2204356

Product dimensions:




- Overall Height / projection: 356 mm
- Exit reach: 194 mm
- Exit height: 226 mm
- Centre distance(s): n/a
- Base diameter(s): 45 mm
- Recommended hole diameter: Ø35 mm
- Max. surface depth: 35 mm
- Spout diameter: 22 mm
- Spout aerator size: M22 x 1 F

Packaged properties:

Box length: 420 mm
Box width: 235 mm
Tap only weight: 1.35 kg

Box depth: 75 mm
Units per outer: 5
Boxed weight: 1.66 kg

Product flow characteristics:



- Min / Max water pressure: 0.30 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 17.70

- Control valve type: 1/2" Ceramic disc QT
- Flow characteristics: Dual flow (H/C)
- Non return valve(s): None

- Aerator type: Honeycomb aerator
- Spout connection method: Locking Collar

- Tail pipe inlet / outlet size: M12 / 1/2" bsp female
- Inlet pipe type / length: Flexible stainless braided hose / 255 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year