

VESSEL SINK

INSTALLATION INSTRUCTIONS

Please read all instructions carefully before installation.

IMPORTANT: Professional installation is recommended. Inspect the sink for shipping damage before installation. Natural stone products may vary in color, veining, texture, and mineral markings.

1. BEFORE YOU BEGIN

- The countertop surface must be flat, stable, and capable of supporting the full weight of the sink.
- The drain hole in the countertop must be properly prepared and aligned with the sink drain opening.
- A compatible non-overflow drain is recommended for this product.
- For sinks made of natural stone, slight variations in color, veining, texture, mineral marks, and small natural pores are normal and are not considered defects.
- Inspect the sink carefully before installation. If the product has been damaged during shipping, do not install it. Contact the seller immediately.

2. TOOLS AND MATERIALS REQUIRED

• Measuring tape	• Pencil or marker
• Neutral silicone sealant or glass adhesive	• Drain assembly
• Wrench	• Clean cloth or paper towel
• Level (optional)	• Hole-cutting tool (if drilling is required)

3. INSTALLATION PROCEDURE

STEP 1 – DETERMINE THE INSTALLATION POSITION

Place the vessel sink on the countertop in the desired position. Check the sink orientation, the distance from the wall, faucet alignment, and the overall visual balance on the countertop. Make sure the sink is centered properly and that there is enough space for comfortable daily use.

STEP 2 – ALIGN THE DRAIN OPENING

Confirm that the drain opening at the bottom of the sink is aligned with the drain hole in the countertop. If the countertop has not yet been drilled, measure the exact center point of the sink drain opening and cut the hole accordingly.

STEP 3 – INSTALL THE DRAIN ASSEMBLY

Insert the drain body through the sink drain opening. Install the sealing gasket, lock nut, and other drain components according to the drain manufacturer's instructions. Tighten securely, but do not overtighten, as excessive force may damage the sink.

STEP 4 – APPLY SEALANT

Apply a continuous bead of neutral silicone sealant or glass adhesive around the contact area between the bottom of the sink and the countertop. This helps improve stability, creates a better seal, and reduces the risk of water seeping beneath the sink.

STEP 5 – POSITION AND SECURE THE SINK

Carefully place the sink onto the countertop. Make sure the drain opening is correctly aligned with the countertop hole. Gently adjust the sink until it is level, centered, and properly seated. Apply light pressure to ensure full contact between the sink base and the countertop surface.

STEP 6 – CONNECT THE DRAIN PIPE

Connect the drain assembly to the drain pipe and secure all fittings properly. Check all connections to make sure they are correctly installed. If a faucet is being installed at the same time, complete the water supply connections according to the faucet manufacturer's instructions.

STEP 7 – REMOVE EXCESS SEALANT

Before the sealant cures, use a clean cloth or paper towel to remove any excess sealant around the base of the sink. This helps maintain a clean and professional finished appearance.

STEP 8 – ALLOW TO CURE AND TEST

After installation is complete, allow the sealant to cure fully according to the sealant manufacturer's recommendations. Once fully cured, turn on the water supply, check that water drains smoothly, and inspect the drain assembly, drain pipe, and the area around the sink for leaks.

4. IMPORTANT SAFETY AND INSTALLATION NOTES

- Professional installation is recommended.
- Handle the sink with care during transportation and installation. Avoid dropping or striking the product.
- Do not use strong acidic or alkaline cleaners, as they may damage the surface finish.
- Natural stone sinks may show variation in pattern, tone, veining, and mineral texture. These are natural material characteristics and not quality defects.
- If drilling is required in stone, wood, or composite countertops, installation by a qualified professional is strongly recommended.
- Do not overtighten metal hardware or fittings, as this may cause cracking or other damage.

5. CARE AND MAINTENANCE

- Clean regularly with a soft damp cloth.
- Use a mild, pH-neutral cleaner when needed.
- Keep the sink dry after use to help maintain its appearance.
- Avoid contact with sharp or heavy objects that may scratch or damage the surface.

NOTICE

Product appearance may vary slightly due to lighting, photography, and the natural characteristics of the material. For natural stone sinks, each piece is unique in color and pattern.