


# Assembly Instruction Sheet for Model HL371602

## Package Contents

Part	Description	Quantity
A	Fixture Body	8 pcs.
B	Mini Canopy	8 pcs.
C	Lock Cap	8 pcs.
D	Cord Grip	8 pcs.
E	Ceiling Canopy	1 pc.
F	Mounting Bracket	1 pc.



### STEP 1

Thread the hanging cord of Fixture Body(A) through the Mini Canopy(B).  
Thread the hanging cord of Fixture Body(A) through the Lock Cap(C) and Cord Grip(D).  
Screw the Lock Cap(C) to the Cord Grip(D) to position Fixture Body(A) to the Ceiling Canopy(E).

### STEP 2

Remove the Mounting Bracket(F) from Ceiling Canopy(E).  
Mark the drilling position on ceiling with the help of the Mounting Bracket(F).  
Drill holes on the marks and stick the expansion anchors into the holes.  
Fix the Mounting Bracket(F) to the expansion anchors with self-tapping screws.

### STEP 3

Connect wire color Black/Red of Fixture Body(A) as one strand of wire.  
Connect wire color White/Blue of Fixture Body(A) as the other strand.

### STEP 4

Hold the fixture close to ceiling.  
Connect live line to wire color Red from the hanging cord of Fixture Body(A).  
Connect neutral line to wire color Blue from the hanging cord of Fixture Body(A).

### STEP 5

Attach the Canopy(E) to the Mounting Bracket(F).

### STEP 6

Drill holes in the right places on ceiling.  
Fix the Mini Canopy(B) to the holes with self-tapping screws .

### STEP 7

Insert your bulb to the bulb base.

Your fixture is now assembled and ready to use.