



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11697 - 15 Watt LED Direct Wire Downlight; 6-Inch; Dual Dimming; Round; with Integrated Emergency and Test Switch

- Wattage Selectable
- CCT Selectable
- Has Emergency Battery
- Air Tight
- Flicker Free
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	15W/11W
Volts:	120V-277V
Lumens:	1350L/1050L
CRI:	90+
R9 Value :	50
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	108
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Dual Dimming; Forward or Reverse at 120V/0-10V at 120-277V
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Dual Dimming; Forward or Reverse Phase at 120V/0-10V at 120-277V
Incandescent Equivalent :	85W
Operating Temperature :	-4F to +104F (-20C to +40C)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<30%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923116971
Each Quantity:	1
Each Dimensions:	8.27 x 4.72 x 6.89

PHYSICAL

Finish:	White
Lens Finish:	Matte Frosted
Lens Material:	Acrylic
Dimensions:	H:1.34" DIA:6.77"
Weight (Lbs.):	3.04
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	6.19 in. Cutout
Max Drywall Thickness:	1 in.
Clearance Height:	3
Sloped Ceiling Compatible:	Yes

COMPLIANCE

Safety Listing:	cETLus - Certified
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4517253
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
ADA Compliant:	No
Closet Rated:	Yes
FCC Compliant:	Yes
IP Rating:	IP44
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Default Wattage: 15W; Battery Weight: 0.62lbs
Specification Note:	Plenum Rated FT6 Cable; Integrated Emergency Driver and Test Switch; Fixture produces 500lm under emergency battery power; Wattage increases by 5W during charging periods.
Integrated Features:	Emergency and Test Switch

ACCESSORIES

	80-866	6-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3.5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-944	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter
	80-947	6" Goof Ring for Remote Driver Installation
	80-952	New Construction Mounting Plate for Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.5-inch hole diameter
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	86-216	Temporary work Light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts; Frost Finish