

NEOLO ELONGATED FLUSH VALVE TOILET

- Elongated flush valve toilet
- Vitreous china
- Low consumption (6.0 Lpf/1.6gpf)
- Wall outlet elongated bowl, angle back and base
- Siphon jet flush action
- Fully glazed 2" trapway
- 12" x 9" water surface area
- 1-1/2" inlet spud
- 4 bolt caps

- 2529.116** Elongated bowl only, top spud, wall outlet
- 2530.116** Elongated bowl only, back spud, wall outlet
- 2531.116** Elongated bowl only, back spud, wall outlet, integral seat

Nominal Dimensions:

632 x 356 x 356mm
(24-7/8" x 14" x 14")

Recommended working pressure –
between 25 psi at valve when flushing
and 80 psi static

Fixture only, less seat and flush valve

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2 for Vitreous China Fixtures



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White
- Seat:
 - American Standard #5901.100
Heavy duty open front less cover
 - American Standard #5905.100
Extra heavy duty open front less cover
- Flush Valve:
 - Sensor-Operated: American Standard Selectronic[®]
DC Power #6065.161.002 (Top Spud)
 - Sensor-Operated: American Standard Selectronic[®]
AC Power #6067.262.002 (Back Spud)
 - Manual: American Standard #6047.161.002
(Top Spud)

