



see what Delta can do™

## PENDANT RAINCAN SHOWER HEAD

- H<sub>2</sub>Okinetic® Pendant Raincan
- Single-Setting Shower Head
- LED light on each spray face

### FEATURES:

- H<sub>2</sub>Okinetic® Technology

### STANDARD SPECIFICATIONS:



- Max flow rate 1.75 gpm @80 PSI, 6.6 L/min @ 550 kPa
- Adjustable pendant shower heads for ideal coverage
- To be used with a 9' (2286 mm) ceiling or taller
- Connects to 1/2" IPS male threads
- LED lights are powered by hydrogenerator. No batteries required.
- Spray settings include: H<sub>2</sub>Okinetic® spray

### WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to [www.deltafaucet.com](http://www.deltafaucet.com) for the complete details of our limited warranty.

### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1



▲ Designate proper finish suffix

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-B-57140-25-L Rev. B

### Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2025 Delta Faucet Company