oject:	
xture Type:	
ocation:	
ontact:	

Wall mounted · Damp location listed



Description:

These fixtures feature a modern repeating circular frame. Etched opal glass shades are seamlessly secured to provide a clean, contemporary look to your home. The modern LED source delivers crisp, high quality lighting that is the perfect choice for both general and task lighting.

Specifications:

- · Brushed Nickel (-009) (plated)
- · Steel construction
- · Etched Opal glass diffuser
- · These fixtures have a pleasing familiarity within a modern repeating circular frame
- · Etched opal glass shades are discreetly secured with no visible fittings.
- The modern LED source delivers crisp, high quality lighting that is the perfect choice for both general and task lighting in bath or powder rooms
- · Part of the Design Series Collections offering high style and design.
- · Can be mounted vertical or horizontal.
- · 624 lumens 66 lumens/watt
- · 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified

Performance:

Number of Modules	2
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	624/66 (LM-79)
ССТ	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30° C
Warranty	
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

Images:



Dimensions:

Width: 16" Depth: 4-5/8" Height: 5-1/2"

H/CTR: 2-3/4" (vertical)

Dimming Notes:

This light is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.