

IMPORTANT SAFETY INSTRUCTIONS

- To avoid injury or damage, mount only on a surface that is sturdy.
- To avoid electric shock, make sure the electricity is turned off at the main circuit breaker panel. If you are replacing an existing fixture, turn off the following in order: fixture, wall switch, and main fuse or breaker box.
Note: Some types of fuses must be unscrewed to shut the power off.
- If you are unclear as to how to proceed, please consult a licensed electrician.

UNPACK THE FIXTURE: Check the contents of the box. Box should contain all items on the parts diagram.

INSTALLATION INSTRUCTIONS

1. Measure Canopy (D) height with measuring tape. Adjust Canopy Screws (E) on Mounting Plate (A) to the height of measured Canopy (D) plus 1/4" to allow them to protrude through Canopy (D) during installation. Lock Canopy Screws (E) in place with the hex nuts.

2. Secure Mounting Plate (A) to the junction box (not included) using Mounting Screws (B) provided. Ensure Mounting Plate (A) is positioned with the threads of Canopy Screws (E) pointing down towards the floor.


3. Adjust Wire (H) to desired hanging length using the side screw on Wire Grip (G). Remove any excess Wire (H), leaving approximately 10 inches beyond desired hanging length.

Note: Apply gentle pressure when removing/replacing screw to avoid stripping.

4. Place Canopy (D) flush against the ceiling with Canopy Screws (E) protruding through the holes in Canopy (D). Verify that 1/4" of the threaded portion of Canopy Screws (E) are visible. Remove Canopy (D) and set it aside.

Note: If 1/4" of Canopy Screws (E) are not visible, remove Canopy (D) and re-adjust Canopy Screws (E) to proper height and lock them in place with the hex nuts.

5. Using the wire graph below, connect the appropriate wires from the fixture to the corresponding wires in the electrical junction box (not included) and secure Wire Connectors (C).



- A.** Connect the ground wire (bare copper or green) from your fixture to the:
- 1) ground wire in the junction box, or
 - 2) ground screw in the junction box
- B.** Connect the BLACK house wire to fixture hot wire that corresponds to diagram (black, round & smooth, white/grey with tracer, brown/gold without tracer).
- C.** Connect the WHITE house wire to fixture neutral wire that corresponds to diagram (white, ribbed/ridged, white/grey without tracer, brown/gold with tracer).

- 6.** Place Canopy (D) against the ceiling, ensuring Canopy Screws (E) are protruding through the holes in Canopy (D). Secure Canopy (D) and the fixture in place with Decorative Caps (F).
- 7.** Gently remove plastic insert from Grip Screw (I) with a screwdriver. Loosen Grip Screw (I) by turning in counter-clockwise direction. Lift Grip Screw (I) and Socket Cap (J) to expose Shade Screws (K).
- 8.** Install light bulb (not included) into Socket Assembly (L).
- 9.** Place Socket Assembly (L) into Shade (M) and secure in place with Shade Screws (K). Tighten each screw evenly to ensure the shade hangs straight.
Note: Shade Screws (K) may need to be adjusted to fit into shade.
- 10.** Place Socket Cap (J) over Shade Screws (K) and secure in place with Grip Screw (I). Secure plastic insert into Grip Screw (I).

Enjoy your new fixture!

HELPFUL TOOLS: Safety Goggles, Screwdriver, Ladder, Measuring Tape

