

K-32619

1-1/4" x 36"-60" linear drain channel

Features

- Flush-to-wall design (recommended) provides a clean aesthetic; can also be installed within shower floor interior.
- Extend channel length from 36" to 60" for easier specification and precise wall-to-wall installation (if desired)
- Channel is pitched to outlet for easy cleaning and complete drainage; handles up to 15 gpm (56.8 lpm) flow capacity (rate may vary by installation)
- Drain outlet location can be adjusted to bypass joints, venting, or other in-floor obstacles
- Outlet adapter can be preattached to drain pipe for simplified installation and access to couplings
- Easy-clean domed hair strainer prevents clogs
- Subfloor brackets are height-adjustable to ensure the drain channel is mounted at the correct height during installation
- Removable tile guide/mud guard keeps channel clean of debris during installation and provides a straight edge to tile against
- Wide-top flange with protective film ensures excellent waterproof adhesion
- Can also be installed with KOHLER side-outlet adapter K-28987 (sold separately)
- Requires Kohler 1 1/4" x 36", 1 1/4" x 48", or 1 1/4" x 60" linear drain grate



Available Colors/Finishes

Color tiles intended for reference only.

NA NA Not Applicable



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-30-2026 03:14 - US-CA

THE BOLD LOOK
OF **KOHLER®**

Codes/Standards

ASME A112.18.2/CSA B125.2

Material



- Solid stainless steel and brass construction
 - KOHLER finishes resist corrosion and tarnishing
-

Warranty

See website for detailed warranty information.

KOHLER® One-Year Limited Warranty





Installation

- Through-the-floor, installed with tile

Installation Notes

Install this product according to the installation instructions.

