

When Quality Counts, It's

TivoliTile™ Self-Adhesive Vinyl Floor Tiles

Easy Do-It-Yourself Installation

IMPORTANT: Make sure the **PATTERN** number located on the side of this box is the same when using two or more boxes. Before installing the tiles, store them at room temperature for at least a day.

1. Preparing the Surface

ALL floor surfaces **MUST** be dry, clean, smooth and level.

- **Cement:** Fill in all cracks and holes with a suitable latex filler.
- **Wood:** Make sure all planks are securely nailed down. Countersink nail heads, and cover with latex filler. The surface must be completely clean and free of paint, varnish, or wax.
- **Resilient Vinyl:** Remove all dirt, grease, or wax build up.

Do NOT install tiles over cushioned vinyl rubber flooring. Remove flooring or cover with plywood. If installing plywood, remember to countersink the nails and cover the holes with filler.

DO NOT INSTALL TILES OVER:

- Any floor exposed to excessively hot or cold temperatures.
- Any floor exposed to excessive moisture.
- Radiant heated floors.
- Particle board.

2. To Begin:

You must determine the center point of your room. Measure the center points of opposite walls and secure a chalk line from one to the other. Repeat the process with the other set of opposite walls. The point at which the chalk lines intersect is the room's center. (Figure 1)




Figure 1

3. Tile Installation:

Wherever tiles are marked with arrows in the back, install them so that all arrows point in the same direction. Starting at the center point as shown in Figure 1, peel off the protective paper and carefully align the tile with the chalk line markings. Press down firmly. (Caution: the tile's protective paper covering is very slippery. To avoid accidents, do not leave the paper on the floor after you've peeled it from the tile.)

How Many Do You Need

	6'	8'	10'	12'	14'	16'	18'	20'
6'	2	2	2	3	3	4	4	4
8'	2	3	3	4	4	5	5	6
10'	2	3	4	4	5	6	6	7
12'	3	4	4	5	6	7	8	8

Moving along the chalk line, butt each tile squarely and as tightly as possible. Without going directly against the wall initially, form an "L" shape as shown in Figure 2.




Figure 2

Cover a quarter of the surface area at a time. Do not install tiles to the edges of the room until the main floor area has been covered.

4. Cutting Tiles:

Tiles should be cut with a straight edge and utility knife. (Do not cut over newly installed tiles as the blade may damage the new tiles.) Cut edges should face the wall. If possible, slide cut edges under wall molding.

To fit tiles around irregularly shaped objects, make a pattern of the exposed area with a sheet of paper. Use the paper cut-out as a template. Placing the paper cut-out on the front side of the tile, trace the contours of the paper onto the tile. Cut around the marked contours.

5. Maintenance:

While TivoliTile floors require minimum maintenance, please follow these guidelines:

- Sweep, damp mop, or vacuum regularly.
- Avoid abrasive cleansers.
- Use furniture leg coasters.
- Occasionally use an appropriate vinyl tile cleaner.
- **DO NOT WAX.** This will make the floor's surface too slippery and may cause accidents.

ACHIM IMPORTING, INC.

58 Second Avenue
Brooklyn, NY 11215
MADE IN CHINA
V-25G

