

# LED Flush Mount

LED New Construction and Remodel • Damp Location • Dimmable •



## Specifications:

### Description:

LED Flush Mount provides versatile lighting in line voltage. Acrylic diffuser eliminates glare. Decorative, contemporary design for ceiling or wall applications. Available in three sizes.

### Features:

Easy to install diffuser  
With magnetic PCB light source  
Ceiling surface mounting

### Performance:

Input Power	15W / 20W / 35W
Input Voltage	120V
Input Frequency	60Hz
Initial Lumens	1120 / 1500 / 2620
Deliver Lumens	900 / 1200 / 2100
CCT	3000K
CRI	90+
LPW	60
Life Hour	50,000 hrs
Warranty	3 years Limited
Dimension	10"x3.8", 14"x3.8", 17"x3.8"
Certification	cETLus Classified. Damp Location
Accessories	P3 Connector × 3 Dia. 0.15" x 0.95" L Screw × 2

### Catalog Number:

Base	Finish	Color Temp.	CRI	Voltage
	Bronze	3000K/4000k	90+	120V
	Nickel	3000K/4000k	90+	120V
	Bronze	3000K/4000k	90+	120V
	Nickel	3000K/4000k	90+	120V
	Bronze	3000K/4000k	90+	120V
	Nickel	3000K/4000k	90+	120V

### Image:



### Electrical Data:

Input Voltage	120V
Input Frequency	60Hz
Power Factor	≥0.90
Temperature	-25°C to 40°C
Dimming	Yes