



TL5500 & TL5502

2" wide x 2.25" high  
(50mm x 57mm)



TL5520 & TL5522

2" wide x 2" high  
(50mm x 50mm)



TL5550 & TL5552

2" wide x 1-3/4" high  
(50mm x 46mm)



TL5570 & TL5572

2" wide x 2-1/8" high  
(50mm x 54mm)

## Features

- Standard MR16 sizing
- GU10 - 120v & GU5.3 - 12v bases
- Glass and forged aluminum housings
- High brightness COB LED
- 3 year warranty
- Indoor use - track lighting, recessed down lighting, pendant lighting
- Outdoor use - landscape lighting, down light fixtures, spotlights

Item No.	Input Voltage	Input Power	Incandescent Equivalent	Base	CCT	Lumens	CRI	Beam Angle	Dimming	Case Quantity	Lens	Rated Life
TL5500	120V	6W	50W	GU10	2700K	500lm	90	36°	Yes	12	Clear	25,000 hours
TL5502	120V	6W	50W	GU10	2700K	480lm	80	36°	Yes	12	Clear	
TL5520	12V	7W	50W	GU5.3	2700K	630lm	80	36°	Yes	12	Clear	
TL5522	12V	7W	50W	GU5.3	2700K	480lm	90	36°	Yes	12	Clear	
TL5550	12V	5W	35W	GU5.3	2700K	430lm	80	24°	Yes	12	Clear	
TL5552	12V	5W	35W	GU5.3	2700K	430lm	80	36°	Yes	12	Clear	
TL5570	120V	5W	35W	GU10	2700K	380lm	80	24°	Yes	12	Clear	
TL5572	120V	5W	35W	GU10	2700K	380lm	80	36°	Yes	12	Clear	

### Exclusively Distributed by:

Acclaim Lighting, Inc. • 1500 Cherokee Parkway, Suite 100, Acworth, GA 30102  
P: 866-845-5451 • Email: service@acclaim-lighting.com • www.acclaim-lighting.com