


The Sumatran Shelter | 44mm Log Cabin (for BBQs, Hot Tubs or Cars) - Technical Data Sheet



- Superior Grade 44mm Finish Interlocking Logs
- Pressure Treated Bottom Logs to Prevent Moisture Penetration
- Heavy Duty 19mm T&G Roof
- Easy To Assemble Interlock System
- High Grade European Softwood

Cladding Material	Heavy Duty Interlocking T&G Logs	Cladding Thickness	44
Framing Style	Tanalised Bearers Only	Framing Size	58mm x 44mm
Roof Material	T&G Boarding	Roof Thickness	19mm
Floor Material	No Floor	Floor Size	0mm
Door Style	Opening Only	Door Size	0mm x 0mm
Window Style	n/a	Window Size	0mm x 0mm
Glazing Thickness	0	Glazing Material	n/a
Roof Covering	Black Mineral Felt	Treatment	Untreated
Locking System	None	Material	Selected European Softwoods



Building Dimension	Length	Width	Base Size	Internal Size	External Ridge	External Eaves	Internal Ridge	Internal Eaves	Ext. Size exc. Roof	Ext. Size inc. Roof	No. of Windows	Weight
10x10 Sumatran Shelter	2950mm	2950mm	2760mm x 2760mm	2672mm x 2672mm	2726mm	2189mm	2514mm	2189mm	2950mm x 2950mm	3150mm x 3150mm	0	544kgs
12x10 Sumatran Shelter	3550mm	2950mm	3360mm x 2760mm	3272mm x 2672mm	2726mm	2189mm	2514mm	2189mm	3550mm x 2950mm	3750mm x 3150mm	0	631kgs
12x12 Sumatran Shelter	3550mm	3550mm	3360mm x 3360mm	3272mm x 3272mm	2829mm	2189mm	2617mm	2189mm	3550mm x 3550mm	3750mm x 3750mm	0	751kgs