Project:		
Fixture Type:		
Location:		
Contact:		

Ceiling mounted • Dry location listed





Specifications:

Description:

One-light LED Mini-Pendant

Construction:

Brushed Nickel

Steel construction

Glass: Clear glass shade

LED Module is replaceable Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Canopy covers a standard 4" hexagonal recessed outlet box

8" 9 gauge chain supplied

Mounting strap for outlet box included

10 feet of wire supplied

Brushed Nickel finish

Modern silhouette with a sleek linear frame

Clear outer glass

Inner etched white glass shade

Replaceable AC LED module

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 5-3/4" Height: 9-1/2"

Overall ht. w/stem: 75-1/2"

Catalog number:

Finish	Color Temp	CRI
Brushed Nickel	30	90 CRI