

ASSEMBLY INSTRUCTIONS

ITEM NO: FX-3817-4

CAREFULLY PLACE ALL PARTS ON A SMOOTH SURFACE AND LAY THEM UP PER THE SKETCH BELOW.

FIXTURE ASSEMBLY

1. LINE UP HOLES IN PULL ROD WITH HOLES IN METAL BASKET THEN SECURE WITH SCREWS AS SHOWN.
2. LINE UP HOLES IN PULL ROD WITH HOLES IN METAL PLATE THEN SECURE WITH SCREWS AS SHOWN.
3. LACE FIXTURE WIRE AND GROUND WIRE UP THROUGH METAL BASKET, METAL PLATE, SHADE AND CHAIN LOOP, THEN SECURE WITH CHAIN LOOP.
4. DETERMINE THE LENGTH OF CHAIN REQUIRED TO HANG THE FIXTURE AT THE DESIRED HEIGHT. USING QUICK LINK ATTACH TO THE CHAIN LOOP ON TOP OF THE FIXTURE. REMOVE OR ADD CHAIN AS DESIRED AT THIS TIME. LACE FIXTURE WIRE AND GROUND WIRE UP THROUGH EVERY OTHER LINK OF CHAIN.
5. ATTACH THE CROSSBAR TO THE J-BOX USING THE TWO SCREWS PROVIDED WITH THE J-BOX. (NOTE: IF THE SCREWS WITH J-BOX ARE TOO SHORT, USE THE SCREWS PROVIDED IN THE MOUNTING HARDWARE PACKAGE)
6. PULL THE EXISTING ELECTRICAL WIRES OUT THE J-BOX AND MAKE PROPER CONNECTIONS USING WIRE CONNECTORES.
7. POSITION CANOPY OVER CROSS BAR AND THREAD SCREW COLLAR LOOP ON THE NIPPLE TIGHTLY.
8. INSTALL A 60 WATT MAXIMUM TYPE "B" BULB (NOT INCLUDED) INTO EACH SOCKET.

ENJOY YOUR LAMP!!

Use Max 4x60W type B bulb
(bulbs not included)

WARNING

- * To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
- * Installation must be performed by a qualified electrician.
- * Turn off the main power at the circuit breaker before installation, replacing lamp or maintenance.
- * Use UL listed wire connectors for connections.

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

