

PHC61G-SCR610BLSTACK



74" x 24" x 23.5" (H x W x D)

Glass door warming cabinet PHC61G stacked with SCR610BL commercial beverage center

Highlights:

- Combines our popular commercial beverage center with our leading blanket warmer
- Glass door warming cabinet keeps full blanket inventory in easy view
- Digital controls for both units ensure easy temperature management

Product Features:

Space-saving design	Allows you to create a full refrigerator-blanket warmer combination with independent controls in a slim-fitting footprint
Slim 24" footprint	Ideally sized for use in space-challenged facilities
SCR610BL display refrigerator	5 cu.ft. commercial all-refrigerator with digital controls and automatic defrost operation for low maintenance storage with full visibility
PHC61G warming cabinet	PureTherm glass door warming cabinet with 5 cu.ft. interior to hold blankets at their ideal temperature
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator and place and secure the warming cabinet on top
ENERGY STAR qualified (refrigerator only)	SCR610BL meets ENERGY STAR standards as a commercial refrigerator
Stainless steel interior (both units)	Offers lasting durability and improved sanitary conditions
Stainless steel trimmed double pane tempered glass door (both units)	Heat-safe doors offer a full view of both interiors
Adjustable cantilevered shelves (both units)	Cantilevered chrome shelving offers a variety of configurations to accommodate different sized items

PHC61G-SCR610BLSTACK Specifications:

Overview	
Height of Cabinet	74.0" (188 cm)
Width	24.0" (61 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.38" (64 cm)
Depth with door at 90°	45.5" (116 cm)
Capacity	10.0 cu.ft. (283 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.5
Voltage/Frequency	115 V AC/60 Hz
Estimated Time to Ship	Out of stock; ETA 3/9/2020
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Warming & Cooling Cabinet	
Top Unit	Warming Cabinet
Door Swing (Top Unit)	RHD
Reversible (Top Unit)	Yes
Adjustable Shelves (Top Unit)	Yes
Shelf Type (Top Unit)	Chrome
Shelf Quantity (Top Unit)	2
Thermostat Type (Top Unit)	Digital
Temperature Range (Top Unit)	120 to 150°F
Interior height (Top Unit)	26.0" (66 cm)
Interior Width (Top Unit)	20.0" (51 cm)
Interior Depth (Top Unit)	19.5" (50 cm)
Capacity (Top Unit)	5.0 cu.ft. (142 L)
Refrigeration Unit	All-Refrigerator
Door Swing (Bottom Unit)	RHD

Reversible (Bottom Unit)	Yes
Adjustable Shelves (Bottom Unit)	Yes
Shelf Type (Bottom Unit)	Chrome
Shelf Quantity (Bottom Unit)	3
Interior Light (Bottom Unit)	Yes
Thermostat Type (Bottom Unit)	Digital
Temperature Range (Bottom Unit)	36°F to 43°F
Interior Height (Bottom Unit)	25.0" (64 cm)
Interior Width (Bottom Unit)	19.38" (49 cm)
Interior Depth (Bottom Unit)	17.38" (44 cm)
Capacity (Bottom Unit)	5.0cu.ft.
Refrigerant Type	R600a
Refrigerant Amount	0.99 oz.
High Side PSI	270.0
Low Side PSI	105.0
Fan Type	Interior and Exterior

