


Operation instruction for semi-auto



1. Choose a suitable location
Place the car umbrella upright on the sunroof glass, with the handle facing towards us.



2. Unhook the hook on the anti-theft rope
Loosen the hook on the anti-theft rope and check if the frame is wrapped by the windproof rope.



3. Pull down the wrench
Pull down the suction cup wrench and cannot pull the car umbrella, it means that the suction cup installation is complete



4. Insert the anti-theft rope into the car door
The anti-theft rope is embedded with soft steel wire, which plays a role in anti-theft after being inserted into the car door.



5. Open the car umbrella
1. Pull the front and rear ends of the car umbrella with your hand, gently it is very easy to pull open with hydraulic assistance.
2. Press the hydraulic lever left, right or above. The position can also be easily opened.



6. Install all windproof ropes properly
Complete installation
Finally, install all windproof ropes and tighten them appropriately to achieve the best windproof effect.

Extended functionality
Courtyard leisure

Storage operation: please refer to the diagram for reverse operation.



warranty

1. Product failure and damage caused by failure to install, use, maintain and keep the product in accordance with the requirements of the user manual have exceeded the warranty and warranty period.
2. Without the consent of the company, do STH without authorization changes to the product inherent set or do STH without authorization from teardown repair: accidental factors or human behavior result in product failure or damage, such as inappropriate input voltage, high temperature, water, mechanical damage, broken, product serious oxidation and rust, etc.
3. The product is transported and loaded on the way back from the customer for repair
4. Product failure or damage caused by force majeure such as typhoon, earthquake, flood, fire and lightning strike.
5. Failure or damage caused by other non-product design, technology, manufacturing, quality and other problems.

PRECAUTIONS WHEN USING THE CAR SUNSHADE

1. Do not operate the vehicle with the sunshade installed.
2. By fixing by a suction plate to the top of the roof of the car, even if they are specific cases, in paintings damaged or poor adhesion may leave scratches or marks pressure due to air compression.
* Having been sufficiently informed of this, the problems caused by this reason will not be covered by our return and guarantee policy.
3. The suction rubber must be clean and free of dust, stones, pollen, etc so that its holding power is high and prevent it from falling.
4. To prevent the wind from blowing the SUNSHADE, they must be taut the braces correctly. It is recommended not to use it when the wind speed is greater than 10 m/s.
* The seller is exempted from any type of responsibility for damage to the product or to the vehicle due to natural disasters and no compensation will be received.
5. Caution. Not intended for use on vehicles with a roof adjustable, roof rails, long antennas and antenna rods.
6. If the vehicle does not have handles on the rear doors, it will be difficult to tighten and therefore cannot be installed.
7. To avoid the formation of mold, the sunshade cannot be stored wet or damp, but should be dried thoroughly before storing.

Garantiekarte

stil

benutzername		Kontakt-telefonnummer	
kaufdatum		E-mail	
Kontakt-adresse			
Produkt-grund			