13-STEP ROLLING STEEL WAREHOUSE LADDER- LAD-13-14-P-EZ *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 10" TYP. 166" 23 9/16" 130" Ø 10' 116 9/16' 120 7/8" DIMENSION TOLERANCE ± 1/4" STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS NOTE REPRESENTED SATISFIES DESIGN AND DIMENSION MODEL NUMBER IS LAD-13-14-P-EZ REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α SOME ASSEMBLY REQUIRED OVERALL WIDTH IS 42 1/4" CONFIRM PRODUCT AND INSTALLATION Ρ **USABLE WIDTH IS 23 9/16"** COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ TOOL TRAY SOLD SEPARATELY AND LOCAL REGULATIONS AND STANDARDS. **OVERALL LENGTH IS 120 7/8"** ANY MODIFIED UNITS ARE NON-RETURNABLE **USABLE LENGTH IS 116 9/16"** 0 SAFETY GATE SOLD SEPARATELY **OVERALL HEIGHT IS 166"** [] As drawn [] As marked V **TOP STEP HEIGHT IS 130"** Α Signed: Date: STEP TYPE IS PERFORATED CLIMB ANGLE IS 50° Printed Name: SPECIAL FEATURES STEP DEPTH IS 7" LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING TOP STEP DEPTH IS 14" NONE DISTRIBUTOR'S NAME: FOR INTERNAL USE ONLY MAX CAPACITY IS 350 LBS W.O.# X PROJECT SIGN OFF VESTIL MANUFACTURING WHEEL SIZE IS Ø10" **SALES** FRONT WHEEL SIZE IS Ø 3" DATE: 7/18/2016 SALES: X ENG. TOUGH BAKED IN POWDER COATED BLUE FINISH SCALE: 1:42 FILE NAME: BOTTOM STEP HAS TOUGH BAKED IN FAB. POWDER COATED YELLOW FINISH Quoted lead time: χ QUOTE # 44-007-561 POWER Χ