




Owner's Manual

with Assembly Instructions

Styles and colo(u)rs may vary.
Made in China.

The owner's manual contains important safety information as well as assembly, use and maintenance instructions.

The Ride-on Car must be assembled by an adult who has read and understands the instructions in this manual.

Keep the package away from children and dispose of properly before use.

Keep this manual for future reference.

On the purchase of your new Ride-On.

This ride-on will provide your child with many miles of riding enjoyment. To help ensure a safe ride we ask you to please read this manual carefully, and keep it for future reference.

Please follow the recommendations in this manual, they are designed to improve the safety and operation of your ride-on car and it's rider.

**HZB-9521 Children Battery Powered Ride-On manufactured by Chizhou Haizhibao Children Products Co., Ltd.
(Add: Matang Industrial Zone, qingyang County, Chizhou City, Anhui Province, P.R.China).**

SPECIFICATIONS:

Battery	18V7AH*2(36V)
Charger	36V1000mA
Input	Depend on local voltage
Motor	775-11000

Suitable age: over 3 years

Load Capacity: Under 50kg

Speed: 4-10km/h

Size of ride-on car: 126*54*77CM

Power way: Charging type

Charge time: 8-12 hours

**WARNING!**

- **CHOKING HAZARD** - Small parts. Not suitable for children under 36 months. The product contains small parts, keep children away when assembling.
- **ADULT ASSEMBLY REQUIRED.**
- Always remove protective material and poly bags and dispose before assembly.
- Protective equipment should be worn. Always wear shoes and sit in the seat when operating the vehicle.
- Only drive on level ground. Never use on the lawn.
- Keep your hands, hair, and clothes away from moving parts.
- Never leave child unattended. Direct adult supervision is required. Always keep child in view when child is in vehicle.
- To reduce the risk of injury, adult supervision is required. Never use in roadways, near motor vehicles, on or near steep inclines or steps, swimming pools or other bodies of water, always wear shoes, and never allow more than 1 rider.
- Never use in unsafe conditions such as snow, rain, loose dirt, mud, sand, or gravel, otherwise may result in an unexpected accident such as tipping over, and could damage the electrical system or battery
- Not to be used in traffic.
- This toy should be used with caution since skill is required to avoid falls or collisions causing injury to the user or third parties.
- This toy is unsuitable for children under 36 months due to its maximum speed; Maximum user weight is 30kg.
- This toy has no brake.

**BATTERY INFORMATION**


- Non-rechargeable batteries are not to be recharged.
- Rechargeable batteries are to be removed from the toy before being charged.
- Rechargeable batteries are only to be charged under adult supervision.
- Different types of batteries or new and used batteries are not to be mixed.
- Batteries are to be inserted with the correct polarity.
- Exhausted batteries are to be removed from the toy.
- The supply terminals are not to be short-circuited.

**WARNING!**

The remote control is not a toy, and is only allowed to be operated by adults.

Parts Diagram | 3

HINT: Some parts shown are assembled on both sides of vehicle














**Assembly tools required
(not included):**




Screwdriver

Parts List | 4


1 Vehicle body x1	2 Steering wheel x1	3 Seat back x1	
			
4 Seat cushion x1	5 Basket x1	6.1 Front wheel x2	6.2 Rear wheel x2
			
7 Wheel cover x4	8 Front bumper x1	9 Front guardx1	
			
10 Rear bracket x1	11 Left bracket connectorx1	12 Right bracket connector x1	
			
13 Motor x2	14 Rear axle x1	15 M10 nut x4	
			
16 M8 nut x1	17 Ø4*30 screw and M4 nut x2	18 Gasket x2	
			
19 Ø4*19 screw x2	20 Ø4*12 screw x6	21 Ø6*16 screw and M6 nut x1	
			



1. First rotate the front axle left and right to insert the red part into the steering shaft, then tighten it with an M8 nut.
2. Insert the $\varnothing 6 \times 16$ screw and tighten the M6 nut of the front axle.




1. First insert the gasket into the front axle.
 2. Insert the front wheel into the front axle.
 3. Insert the M10 nut into the front axle to tighten and fix.
 4. Finally insert the wheel cover into the hub.
 5. Repeat the above procedure to assemble the other front wheel.
- HINT: An extra spanner has been provided to hold the Lock Nut on the other side of the front axle while tightening the Lock Nut on the other side.




- 1.Insert the rear axle.
 - 2.Motor through the rear axle and connect it.
 - 3.Insert the rear wheel into the rear axle.
 - 4.Insert the M10 nut into the rear axle to tighten and fix, do not over tighten .
 - 5.Finally insert the wheel cover into the hub.
 - 6.Repeat the above procedure to assemble the other rear wheel.
- HINT: An extra spanner has been provided to hold the Lock Nut on the other side of the rear axle while tightening the Lock Nut on the other side.


Turn the vehicle body upright




After attach 4 wheels, reverse the vehicle body and then connect the power .




Align the bottom clip slot of the seat back with the rear clip hook on the base, then insert it fully.




Insert the seat cushion into the slot of the seat back.




Use a screwdriver to place the $\varnothing 4 \times 19$ screw into the hole at the front of the seat cushion and tighten it.




1. Tuck the steering wheel wires inside the steering wheel, then install it. Connect the terminal of the steering wheel to the terminal of the instrument panel.
2. Press and hold the two protruding black buttons on the steering wheel, align it with the small hole on the steering column, and then insert it until you hear it "click".




1. Insert the bottom hook into the Front bumper (underneath the front of the vehicle) slot.
2. Tighten the $\varnothing 4 \times 12$ screws.



1. Attach the hook-and-loop fasteners on the cloth bag to the rods one by one in sequence.
2. Put the basket insert into the hole.
3. Use a screwdriver to place the $\varnothing 4 \times 30$ screw into the hole and tighten M4 nut.




Fully insert the front guard into the corresponding hole.




Before installation, please confirm the left and right rear bracket connector are correct and ready.

1. Fully insert the left and right bracket connector into the corresponding holes.
2. Insert the rear bracket into the holes of the connector
3. Use four $\varnothing 4 \times 12$ screws to tighten them.



1. Battery display
2. Volume-
3. Volume+
4. Song
5. Story
6. Song
7. USB card slot
8. TF card slot
9. Aux.



- 1. Power button:** Turns the product on and off.
- 2. Forward/reverse Switch:** Changes the direction that product moves from forward to reverse.
 - To move the product forward, shift the switch to top position.
 - To move the product backward, shift the switch to down position.
- 3. Light switch:** To turn on or off the light.
Speed switch: The driver can choose to use 1st gear (Low) or 2nd gear.

⚠ IMPORTANT

- **Always stop vehicle when changing the speed or direction to avoid damage the gears and motor.**
- **HIGH SPEED (If equipped):** Make sure your child knows how to steer, how to start and stop the product and knows the rules for safe driving.



Use the vehicle on generally level ground **ONLY!**



DO NOT Use the vehicle on Lawn space!

⚠ WARNING!

- **ONLY an adult is allowed charge and recharge the battery!**
- **This product with Charging Protection: when charging, all functions will be cut off.**

- The POWER SWITCH must be turned in OFF position when charging.
- Before the first use, you should charge the battery for 4-6 hours. Do not recharge the battery for more than 10 hours to avoid overheating the charger.
- When the vehicle begins to run slowly, recharge the battery.
- After each use or once a month minimum recharge time as 8 to 12 hours, less than 20 hours at most.
- Use only battery(ies) and charger specified by the manufacturer. Using another battery or charger may cause a fire or explosion. Do not use the battery or charger for any other product.
- If your ride-on with a Digital voltmeter(IF EQUIPPED), the magnitude of voltage will tell you how much power is remaining in the battery when you must recharge the battery. Make sure the vehicle is stop!

12V product	less than 12.5V	The battery needs to be charge.
24V product	less than 24.1V	



1. Plug the charger port into the input socket (the socket is below the seat).
2. Plug the charger plug into a wall outlet. The battery will begin charging.

Battery Disposal



The battery will eventually lose the ability to hold a charge. Depending on the amount of use, and varying conditions, the battery should operate for one to three years.

Important! Recycle the dead battery responsibly. The battery contains lead acid (electrolyte) and must be disposed of properly and legally. It is illegal in most areas to incinerate lead acid batteries or dispose of them in landfills. Take it to a federal or state-approved lead acid battery recycler, such as local automotive battery retailer.

Do not throw the battery away with your regular household waste!

Problem	Possible Cause	Solution
Vehicle does not run	Battery low on power	Recharge battery.
	Thermal fuse has tripped	Reset fuse, see <Fuse>
	Battery connector or wires are loose	Check that the battery connectors are firmly plugged into each other. If wires are loose around the motor contact your distributor please.
	Battery is dead	Replace battery, contact your distributor please.
	Electrical system is damaged	Contact your distributor please.
	Motor is damaged	Contact your distributor please.
Vehicle does not run very long	Battery is under charged	Check that the battery connectors are firmly plugged into each other when recharging
	Battery is old	Replace battery, contact your distributor please.
Vehicle runs sluggishly	Battery low on power	Recharge battery, contact your distributor please.
	Battery is old	Replace battery, contact your distributor please.
	Vehicle is overload	Reduce weight on vehicle.
	Vehicle is being used in harsh conditions	Avoid using vehicle in harsh conditions, see <User Notice>.
Vehicle needs a push to go forward	Poor contact of wires or connectors	Check that the battery connectors are firmly plugged into each other. If wires are loose around the motor, contact your distributor please.
	“Dead Spot” on motor	A dead spot means the electric power is not being delivered to the terminal connection and the vehicle needs repair. Contact your distributor please.
Difficult shifting from forward to reverse or vice-versa	Attempting to shift while the vehicle is motion	Completely stop the vehicle and shift, see <Use Your Ride-On>
Loud grinding or clicking noises coming from motor or gear box	Motor or gears are damaged	Contact your distributor please.
Battery will not recharge	Battery connector or adapter connector is loose	Check that the battery connectors are firmly plugged into each other.
	Charger not plugged in	Check that the battery charger is plugged into a working wall outlet.
	Charger is not working	Contact your distributor please.
Charger feels warm when recharging	This is normal and not a cause for concern	

Completely read through this manual and the troubleshooting guide table before calling. If you still need help resolving the problem **Contact your distributor please.**

- It is parents' responsibility to check main parts of the toy before using, Must regularly examine for potential hazard, such as the battery, charge, cable or cord, plug, screws are fastening enclosure of other parts and that in the event of such damage, the toy must not be used until that damage had been properly removed.
- Park the vehicle indoors or cover it with a tarp to protect it from wet weather.
- Recharge the battery after each use. Only an adult can handle the battery. Recharge the battery at least once a month when the vehicle raider is not being used.
- Do not wash the vehicle with a hose. Do not wash the vehicle with soap and water. Do not drive the vehicle in rainy or snowy weather. Water will damage the motor, electric system and battery.
- Clean the vehicle with a soft, dry cloth. To restore shine to plastic parts, use a non-wax furniture polish. Do not use car wax. Do not use abrasive cleaners.
- When not using, all the electrical source should be turn off. Turn off the power switch and disconnect the battery connection.

Fuse | 16

The battery features a thermal fuse with a reset fuse that will automatically trip and cut all power to the vehicle if the motor, electric system or battery is overloaded. The fuse will reset and power will be restored after the unit is turned OFF for 20 seconds and then turned ON again. If the thermal fuse trips repeatedly during normal use, the vehicle may need repair. **Contact your distributor please.**

To avoid losing power, follow these guidelines:

- Do not overload the vehicle.
- Do not tow anything behind the vehicle.
- Do not drive up steep slopes.
- Do not drive into fixed objects, which may cause the wheels to spin, causing the motor to overheat.
- Do not drive in very hot weather, components may overheat.
- Do not allow water or other liquids to come in contact with the battery or other electric components.
- Do not tamper with the electric system. Doing so may create a short, causing the fuse to trip.



RISK OF FIRE. Do not bypass. Replace only with a new fuse.

If you have any question, please contact at L843485741@outlook.com directly.

**Our products are suitable for
ASTM F963; GB6675; EN71 and EN62115 standard.**