



## PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

## IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

## INSTALLATION STEPS:

- A: Unscrew the decorative nut (8), remove the cover (6),
- B: Insert the two lamp arms (1&24) through the hole on the side of the middle seat (2), and then tighten the nut (3) to fix the lamp arms
- C: Connect 8 brown lamp head wires (4) and one end of brown lead wire (25) with wiring cap (5). Similarly, the other end of the 7 brown lamp head wires (4) and brown lead wires (25) and the brown wire of the main line (11) are tightly connected with the wiring cap (5), paying attention to the bare wire can not be exposed to prevent leakage;
- D: Connect the 8 blue lamp head wires (4) and one end of the blue lead wire (25) with the wiring cap (5). Similarly, the other end of the 7 blue lamp head wires (4) and the blue lead wire (25) and the blue line of the main line (11) are connected tightly with the wiring cap (5), paying attention to the bare wire can not be exposed to prevent leakage;
- E: Pass the cap (6) through the threaded pipe (7), and then lock it with the decorative nut (8);
- F: Thread the main line (11) through the round tube (10), then tighten the round tube (10) onto the threaded tube (9);
- G: Pass the main line (11) through the central hole of the canopy (12), and then tighten the canopy (12) on the round tube (10);
- H: Drill two holes in the ceiling, and then insert the expansion plug (16) into the hole;
- I: Fasten the hanging plate (14) to the ceiling with screws (13);
- J: Connect the main line (11) and ground line (17) to the wire reserved on the ceiling with a wiring bar (15);
- K: Pass the hanging plate screw (18) through the two small holes on the canopy (12), and then tighten the decorative nut (19) to fix the lamp;
- L: Tighten the light source (20) on the lamp holder (21) and try to light it
- M: Press the circlip (22) tightly and install the glass cover (23) into the circlip (22)