

# Assembly Instructions

<u>Parts List</u>	<u>Quantity</u>
Table Top	1 pc
Table Leg	4 pcs
Center Plate	1 pc
#8 Hex Head Short Bolt	4 pcs
#8 Hex Head Long Bolt	8 pcs
Flat Washer	12 pcs
Lock Washer	12 pcs

## ASSEMBLY

We suggest you assemble the product on a soft flat surface to protect the finish. Two people are required to assemble this product.

- Step 1.** Place the TABLETOP face down on a soft flat surface. Attach the LEGS to the table using 8HEX SHORT BOLTS, FLAT and LOCK WASHERS. The lock washer is fitted against the bolt head and the flat washer between the table top and lock washer. Finger-tighten the bolts. Repeat this process for each of the four legs.
- Step 2.** Place the CENTRE PLATE between the four legs. Align the holes and using the 8HEX LONG BOLTS, FLAT and LOCK WASHERS attach to the legs. Use the same process when attaching the bolts. Finger-tighten only at this stage.
- Step 3.** When all bolts and washers are in place, tighten all bolts firmly , but do not over-tighten. Tighten the bolts to the table-top first ensuring that you tighten the bolts in a diagonally opposite order.
- Step 4.** Using 2 people, turn over the assembled table.

### **Caution:**

This unit is manufactured with cast aluminum parts and is brittle. DO NOT force any part of the assembly and DO NOT over-tighten the bolts. This could result in serious damage.



# Assembly Instructions

Parts List	Quantity
Chair Leg with Adjustable Rubber Feet	2
Chair Seat	1
Chair Back	1
Nut	8
Flat Washer	8
Spring Washer	8
Rubber Cap	4

## **ASSEMBLY**

We suggest you assemble this item on a soft surface to protect the finish.

**Step 1.** Place the chair seat face down on a soft flat surface.

Attach the legs to the seat using 4 nut, spring and flat washers. Ensure the spring washer is fitted between the flat washer and the bolt . Finger-tighten only.

**Note that the bolts are already fitted to the side of the seat.**

**Step 2.** Attach the chair back using the nut, spring and flat washers, in the same order as above. Finger-tighten only.

**Step 3.** Stand the unit upright on a flat level surface. Align the sides with seat and back so the unit is level and the legs are parallel, and put the rubber cap on the bolts on the back.

**Step 4.** Carefully tighten the all the nuts to lock the unit in its permanent condition. DO NOT over-tighten.

**Caution:** The unit is manufactured of cast metal parts and is brittle. Do not force any part of the assembly and do not over-tighten the bolts, serious damage can occur.



# Assembly Instructions

## PARTS LIST

1. CHAIR SEAT

2. CHAIR BASE

3. LOCK WASHERS

4. FLAT WASHERS

5. NUTS

6. BOLTS

7. RUBBER HEX CAPS

## QUANTITY

1pc

1pc

4pcs

4pcs

4pcs

4pcs

8pcs

## ASSEMBLY INSTRUCTIONS

We suggest that you assemble the product on a soft surface to protect the finish.

**Caution:** the unit is made of cast aluminum and is brittle. Do not force any part of the assembly and do not over tighten any of the nuts or bolts, as serious damage can occur.

**Step 1.** Take off the chair base from the package, and put in on the ground

**Step 2.** Put the chair seat on the top of the chair base, and Put the bolts through the holes from the top and then have a flat washer, lock washer, and nut to each of the bolts;

Firmly tighten the nuts with a wrench.

**Step 3.** Attach the rubber hex caps to the bolts on the top of the chair base

