



INSTRUCTION MANUAL

♥ Thank you for choosing ♥

NOTICE:

IMPORTANT, KEEP FOR FUTURE REFERENCE PLEASE READ CAREFULLY.


IF YOU HAVE ANY CONCERNS ABOUT THE PRODUCT, PLEASE FEEL FREE TO CONTACT US BEFORE YOU LEAVE A REVIEW.

CAUTION:

1. The installation requests a professional electrician to operate. Please make sure the installation environment ventilating and dry.
2. Wearing gloves during installation to prevent yourself from scratching by the fixtures. or electric wire. Be sure the power has been turned off before operation.
3. Make sure the fixture is away from corrosive chemicals and air such as acid and alkali. Clean the fixture by wiping it with a dry rag.
4. Do not touch the bulb when the fixture is turned on or look directly at the lit bulb. Keep flammable materials away from the lit bulb.
5. To reduce the risk of fire, electrical shock, and personal injury, always turn off and unplug the fixture and allow it to cool before replacing the light bulb.

STEP-BY-STEP INSTALLATION (refer to fig. 1)

1. Shut off the power at the circuit breaker and remove the existing fixture, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts in a clear area, Be careful not to lose any small parts necessary for installation.
3. Connect the tube, to achieve your desired height. (refer to fig 2) Screw the tube into the canopy and lamp body.
4. Remove the mounting screw from the light fixture.
5. Secure bracket to the junction box using junction box screw.
6. Connect the wire (N) from the light fixture to the supply wire (N) from the junction box using a wire connector.
Connect the wire (L) from the light fixture to the supply wire (L) from the junction box using a wire connector.
7. After wires are connected, tuck them carefully inside the junction box.
8. Mount the canopy onto the bracket and secure it with four decorative nuts.
9. Add the **G9** bulbs, and turn on the power, check whether the light fixture works normally or not.
10. Ensure the light fixture work normally, then install the glass. There are two sizes of glass: A, B glass. Put two Silica gel rings on the middle of the glass(refer to fig. 3), and then insert them into the light fixture in order as below picture shown, so that they won't fall off.



Package List:

Lamp body	1	PCS
Long tube	3	PCS
Middle tube	1	PCS
Short tube	1	PCS
Copper	1	PCS
Glass A	4	BAGS
Glass B	7	BAGS
Screw pack	1	BAG
Decorative nuts	4	PCS
Mounting bracket	1	PCS
Canopy	1	PCS
Accessories Bag	1	BAG
Installation Instructions	1	PCS

※The package include extra crystal pieces. The Number of Spare Accessory:

A Ø25xL250mm	4	PCS
B Ø25xL200mm	4	PCS

This product compatible with **G9** bulbs (Not included in the package).

