The sleek and modern design of the G5 Model features a built-in cup holder, a drain collection tank that catches over-flow from the faucets, and a microprocessor control panel.

Filter System Standard Filter G5F Stage 1:5 micron Sediment Stage 2:1 micron Activated Carbon Stage 3: 0.5 micron Post Carbon Reverse Osmosis Filter G5RO Above 3 stages plus Stage 4: 50-GPD RO Membrane

Specifications

Dimension: 13"W x 14"D x 48"H Shipping Weight: 77 lb Cold tank volume: 1 gal Hot tank volume: .5 gal Room temp. tank volume 2.3 gal Cooling Rate 1.5 gal/hr 37-50 °f Heating Rate 1.3 gal/hr 180 °f



Features

Large dispensing gap ideal for filling large bottles Smart technology drip tray lets you know when it needs to be emptied Invisible built in cup holder for flat or cone shaped cups Stainless steel hot and cold tanks

> Model G5 Global Water



PURE, ENDLESS WATER



866-289-7518

3 Stage Filtration or 4 stage Reverse Osmosis Filtration Technology

Stage 1

5 Micron Sediment Filter

The first stage is a 5 micron Sediment filter that helps improve Sediment such as sand, rust and silt that is present in most municipal water sources.

Stage 2

1 Micron Granulated Activated Carbon Filter

The second stage of filtration is a 2 micron, granulated activated Carbon filter. This filter uses an advanced Carbon technology to remove hundreds of cancer-causing constituents such as pesticides, insecticides, petrochemicals, M.T.B.E's, PCB's, defoliants, and benzene.

Stage 3

Reverse Osmosis Technology

The 3rd stage utilizes Reverse Osmosis technology, which removes any molecular compounds smaller in size than water molecules. Such compounds include salt, manganese, iron, fluoride, lead, and calcium.

Stage 4

0.5 Micron Carbon Block Filter

The 4th and final stage is a 0.5 micron Carbon block filter, which gives the water a final "polish". It removes 99% of lead and microbial cysts such as giardia and cryptosporidium. It also ensures that all chlorine has been removed, and that the water entering the holding tanks is completely odorless.

Available options:

Add Nano Silver Carbon Filter. Upgrade to 180GPD Membrane.





Filter life 2500 Gallons or every 6 months Replace (RO) Membrane every 3-4 years

