Project:

Fixture Type: Location:

Contact:

LED FLUSH

Ceiling mounted • Wet location listed



Specifications:

Description:

The all-in-one LED Surface Mount uses an intuitive snap-in system that allows easy flush mount installation to a junction box. 7-1/4" round with decorative glass ring. 3000K, 1050 lumens, 90+ CRI. Dimming with many TRIAC dimmers. Wet location listed.

Construction:

Black (-31) Steel construction Glass: White polycarbonate lens Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes) Title 24 compliant covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied Black finish Flicker free dimming down to 10% Flicker rate less than 30% Intuitive snap-in system

Images:



Dimensions:

Diameter: 7-1/4" Height: 2-3/4"

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	
Input Frequency	
Lumens/LPW	1050/63 (LM-79) per module
ССТ	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	
Labels	cCSAus Wet location listed
	ENERGY STAR [®] qualified

Catalog number:

Base	Finish	Color Temp	CRI
	Black /	3000K	90 CRI