




Product Installation Instructions







Ax2




Bx2




Cx1




Dx1




Ex1




Fx3



Gx1




Hx2




Ix2




Jx4




Kx1









Lx1




Mx2




1

①		Two in one screw (6x28mm)				37pcs +4pcs	
②		Two in one nut (10x12mm)				37pcs +4pcs	
③		Non-slip pads (50x10x2mm)				8pcs +2pcs	
④			Rebound device & Screw (3x16mm)			8pcs +2pcs 2pcs	
			Iron sheet			2pcs	
		Hinge			4pcs	2pcs	2pcs
⑤			Double end connecting line			2pcs	
⑥			Wire clamp			3pcs +2pcs	
⑦			Fixing clip & screw (3x16mm)			20pcs +2pcs	
⑧	Anti Fall Hardware		 x2	(3. 5x14mm)  x2	 x2	 x2 (4x45mm)	 x4
			AC/DC Adapter (12V==2. 0A)				1pcs

Double-head screwdriver, use as required




Product structure decomposition




Use parts ① and ②



Step1




Step2



Step3




Use a screwdriver to lock in the direction of the "+" sign




Disassemble along the direction of "-" sign

Step 1





①





D

4

Step 2



Step 3




Step 4

②



x2




Step 5

②





x2





Step 6

1




Step 7

2




Step 8

③





Tear off release paper and stick the black foot pad on the board





Step 9



①



Step 10



Step 11




Step 12

2




x4




Step 13

Install according to the arrow indications






Step 14





Install according to the arrow indications

Step 15



Step 16




Step 17



2





x4





Step 18



Step 19



Step 20




Step 21

2




x4




Step 22

Install according to the arrow indications





Step 23



Install according to the arrow indications



Step 24



Step 25




Step 26

2




x4




Step 27

⑤  x2




Step 28





Step 29

6  x3




Step 30

7  
x20




Step 31


First, completely unscrew the screws on the parts




Then take out the black rubber pad from the inside of the part, and the white sponge remains unchanged inside the part.




④



x2



x2




Pay attention to the direction of the door hinge, rotate the screws to compress the black gasket, and do not place it in the opposite direction

Place the black gasket on the side where the screws are installed

Step 32


④



x2



x2



Step 33


Pay attention to the direction of
the door hinge during installation

④




x2

When installing a glass door, it is recommended to
have two people install it to avoid the glass door
colliding or hitting oneself.




first




second

After installing the
glass door, place the
black gasket on the
side where the screws
are installed




third

Locking screw




Step 34


The rebound device automatically opens and closes by pressing




Open the glass door




Close the glass door



Step 35




x1



Step 36

8





x2




x2

x2



3.5x14mm

Install the anti fall hardware on the cabinet as shown in the picture first





Pen

Then mark the wall with a pen through the holes in the anti-fall hardware

Step 37


use a ruler to measure the approximate height of the product the wall, and then mark it with a pencil.



Put the expansion bolt into the hole.

Pass the matching screws through the "anti-rewind" and tighten them to fix them on the wall.

Use a tape drill to make holes in the wall that are suitable for the product screws.




User's Guide

Thank you for purchasing this product. To use this product, please plug it into a 12V DC power supply. Please use if the product works normally after connecting to power.

Introduction

The box is an intelligent controller with 2 touch buttons. It can turn ON/OFF the light, change light colors, and adjust the light luminance.

Product Show



ATTENTION PLEASE

1. If there is no touch response suddenly, Re-plug the power to reset the touch static electricity.
2. If bubbles appear on the panel, remove the protective film.

Operation



This touch button is used to turn on/off, change colors, and adjust brightness.

A. Short touch -> lighting on -> short touch -> change light color -> short touch -> change light color -> short touch -> lighting off. B. Long touch -> adjust the luminance



This touch button is used to turn on/off the induction function.

A. Short touch to turn on the induction function. It can auto-turn on the light when people are close to the controller in 1 meters. It can auto power off the light when the body is far away from the controller after 30 seconds.

B. Long touch to turn off the induction function.

C. Note: When you touch the light button to change the light modes, the induction function will automatically turn off. It is best to turn on this function after selecting the light color and adjusting the brightness you want.