

GDC9471 – SINGLE CYLINDER


GDC9471

SPECIFICATIONS

DOOR PREP	Cross Bore 2-1/8" or 1-1/2" Edge Bore 1"
BACKSET	Adjustable to 2-3/8" or 2-3/4"
DOOR THICKNESS	1-3/8"–1-3/4" doors standard thickness Thick door service part available for up to 2-1/4"
CYLINDER	Standard SmartKey Kwikset or Weiser 5pin pin & tumbler available
FACEPLATE	1" x 2-1/4" Square, radius corner and drive-in standard
STRIKES	1-1/8" x 2-3/4" square or round corner
BOLT	1" throw
DOOR HANDING	Reversible for right or left-hand doors
ANSI/BHMA	A156.5 Grade 3
UL AVAILABILITY	Meets 20 minute with Square, Radius, Drive-in latch
ASTM	All Weiser product meets ASTM E 331 water penetration testing


SPECIFICATIONS

PRODUCT DIMENSIONS




	A	B	C	D	E	F
GDC9471	2-1/2"	1-1/8"	2-1/2"	27/32"	5/16"	1-3/4"

6-WAY ADJUSTABLE LATCH



SQUARE CORNER




A 2-3/4" (69.85 mm)


B 2-1/8" (53.975 mm)

C 1" (28.321 mm)

RADIUS CORNER



PRODUCT AVAILABILITY



		 20 min.	Lifetime Brass	Antique Brass	Venetian Bronze	Satin Nickel
GDC9471	Single Cylinder	☐	☐	☐	☐	☐

		 20 min.	Antique Nickel	Polished Chrome	Satin Chrome
GDC9471	Single Cylinder	☐	☐	☐	☐