



Submitted Model No.: _____

Specific Features: _____

52626-▲PK Showerhead

Full Body Spray	Full Spray w/Massage	Fast Massage	Soft Drench Spray	Shampoo Rinsing Spray	Pause	Soft Drench Spray w/Massage

▲ Designate proper finish suffix



SHOWERHEAD

■ Maximum 2.00 GPM @ 80 PSI

STANDARD SPECIFICATIONS

- Max. 2.00 gpm at 80 PSI, 7.6 L/min @ 550 kPa
- Standard 1/2" pipe fitting
- Six spray patterns and pause feature
- The ball joint swivel angle is 20° (10° per side)

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-52626-PK Rev. A



55 E. 111th Street, Indianapolis, Indiana 46280
 350 South Edgeware Road, St. Thomas, ON N5P 4L1
 © 2015 Masco Corporation of Indiana