

the DELUXE SINGLE SWING

Single Swing
A001
A002
A005

Deluxe possesses proven performance. These enclosures surpass the competition with their quality and additional features.



SHOWER ENCLOSURES

BECAUSE THE SHOWER IS EVERYTHING

www.BascoShowerDoor.com | 800.45.BASCO



DELUXE SINGLE SWING

Framed Pivot Door

A001

A002

A005



Features

- Deluxe framed single swing door
- Pull handle
- Pivot hinge with out-swing only
- Tempered glass available in three options
- Easy out-of-square adjustments
- Reversible for left or right installation
- Magnetic latch holds the door securely in place
- Anodized aluminum hardware prevents rusting or corrosion
- Drip system at the bottom of the door includes a channel which returns water back inside the shower

Glass Options

- Clear (CL)
- Obscure (OB)
- AquaGlideXP Clear (XP)

Finish Options

- Silver (SV)
- Brushed Nickel (BN)
- Oil Rubbed Bronze (OR)



Model	Unit Width (Opening Size*)	Walk-thru Opening	Unit Height
• A001-5	27 ¹ / ₄ " - 29"	24 ³ / ₄ " - 26 ¹ / ₂ "	63 ¹ / ₂ "
• A001-8	31 ¹ / ₈ " - 32 ⁷ / ₈ "	28 ⁵ / ₈ " - 30 ³ / ₈ "	63 ¹ / ₂ "
• A001-9	33 ¹ / ₈ " - 34 ⁷ / ₈ "	30 ⁵ / ₈ " - 32 ³ / ₈ "	63 ¹ / ₂ "
• A002-5	27 ³ / ₄ " - 29 ¹ / ₂ "	24 ³ / ₄ " - 26 ¹ / ₂ "	67"
• A002-7	31 ¹ / ₈ " - 32 ⁷ / ₈ "	28 ⁵ / ₈ " - 30 ³ / ₈ "	67"
• A002-8	33 ¹ / ₈ " - 34 ⁷ / ₈ "	30 ⁵ / ₈ " - 32 ³ / ₈ "	67"
• A005-7	27 ³ / ₄ " - 29 ¹ / ₂ "	24 ³ / ₄ " - 26 ¹ / ₂ "	70 ¹ / ₂ "
• A005-11	32 ³ / ₄ " - 34 ¹ / ₂ "	30 ¹ / ₄ " - 32"	70 ¹ / ₂ "
• A005-12	34 ¹ / ₄ " - 36"	31 ³ / ₄ " - 33 ¹ / ₂ "	70 ¹ / ₂ "

*measurements after walls are finished.

Installation Notes

Install this product according to the installation guide.

Applicable Codes/Standards

Specified model meets or exceeds the following:

- ASTM C1464-06 and ASTM C1048
- Safety criteria CPSC16 CRF 1201 categories 1 & 2 and ANSI Z97.1
- SGCC Certification required.

