

Retractable Awning Fabric Technical Specs.



Collections: **Luxury Series**
Classic Series
Slim Gray Series
FS Series

Description

Premium and Top-Quality 100% acrylic fabric, sourced for its soft to touch feel, vivid color saturation, strength, UV protection, breathability, and longevity.



Advaning Fabric Main Features

- 100% Acrylic
- Mold and Mildew Resistant
- UV Protectant
- Lasting Color Retention
- Replacaeble and Recyclable

Fabric Specs.

PREMIUM

TOP-QUALITY

Series	Luxury Series	Classic, Slim Gray, & FS Series	Method/Test
Brand	Recasens Recacryl	Private Label	
Manufactured	Spain	China	
Base of Fabric	Solution Dyed Acrylic	Acrylic	
Weight	9 oz./sq yd	8.25 oz./sq yd	
Finish	Anti-Stain, Rot-Proof	Anti-Stain	
Water Resistant	Excellent	Good	
UV Resistance	1500+ Hours	1500+ Hours	AATCC-16
Abrasion Rating	40K Rubs	30K Rubs	ASTM-4157
Hydrostatic	40.6 cm	25 cm	AATCC-127 B
Puncture Strength	38 lbs.	38 lbs.	ASTM-751
Tear Strength (Warp)	11.5 lbs	12.5 lbs.	ASTM D-2261 • PREMIUM GB/T3917.2-2009 • TOP-TIER
Tear Strength (Fill)	7.7 lbs	6.5 lbs.	ASTM D-2261 • PREMIUM GB/T3917.2-2009 • TOP-TIER
Tensil Strength (Warp)	287 lbs	320 lbs.	ASTM D5034 Grad
Tensil Strength (Fill)	149 lbs	161 lbs.	ASTM D-2594 5804

Accredited Badges

